

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico - December 4, 1951

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

State "Q" well No. 3 in SE SE SE

Company or Operator

Lease

of Sec. 36, T. 16S, R. 30E, N. M., P. M., Lovington Field, Lea County.

N

The well is 330 feet (N.) (S.) of the South line and 330 feet (E.) (W.) of the East line of Section 36.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is _____

Address _____

If government land the permittee is _____

Address _____

The lessee is Skelly Oil Company

Address Box 38 - Hobbs, New Mexico

We propose to drill well with drilling equipment as follows:

Rotary tools from surface to total depth.

The status of a bond for this well in conformance with Rule 89 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
18	13-3/8	44.5#	New	300	Cemented	300
12-1/4	9-5/8	36 #	New	3100	Cemented	1500
7-7/8	5-1/2	17 #	New	8500	Cemented	700

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 8500 feet.

Additional information: Halliburton process will be used on all cementing and cement will be circulated when setting 13-3/8" and when cementing 9-5/8", cement will go to base of 13-3/8".

Approved

except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to:

Name

Skelly Oil Company

Address

Box 38, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

[Signature]
Engineer