## Santa, Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and

OTICE OF INTENTION TO TEST CASING	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
SHUT-OFF	NOTICE OF INTENTION TO PULL OR
OTICE OF INTENTION TO CHANGE PLANS	OTHERWISE ALTER CASING
OTICE OF INTENTION TO REPAIR WELL	
OTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL
Hobbs, N	ew Mexico July 17, 1939
	Place
IL CONSERVATION COMMISSION, anta Fe, New Mexico.	DUPLICATE
entlemen:	do wihad halow at the
entlemen: ollowing is a notice of intention to do certain work as of the wentz "A" State	
Company or Operator Lease	, N. M. P. M., Lovington Field,
Sec. 36 , T. 16 S , R. 36 E	_, N. M. P. M.,
	ROPOSED PLAN OF WORK
at 13" 0.D. 40# casing at 308' in	a shale, cemented by Halliburton on sacks of cement. Cement circulated Stopped plug at 285', left 25' of
et 13" O.D. 40# easing at 308' in 11 Well Cementing Company with 20	n shale, cemented by Halliburton 00 sacks of cement. Cement circulated Stopped plug at 285', left 25' of
et 13" O.D. 40# casing at 308' in Well Communing Company with 20	n shale, cemented by Halliburton 00 sacks of cement. Cement circulated Stopped plug at 285', left 25' of
et 13" O.D. 40# easing at 308' in the little well Commenting Company with 20 around 13" easing to top of hole. Total depth 335' ement in casing. Total depth 335'	a shale, cemented by Halliburton 00 sacks of cement. Cement circulated Stopped plug at 285', left 25' of  JUL 17 1939  HOBBS OFFICE  L.H. Wentz
Set 13" 0.D. 40# casing at 308' in 011 Well Cementing Company with 20 around 13" easing to top of hole. 10 cement in casing. Total depth 335'	a shale, cemented by Halliburton OO sacks of cement. Cement circulated Stopped plug at 285', left 25' of  JUL 17 1939  HOBBS OFFICE  L.H. Wentz
Approved except as follows:	A shale, cemented by Halliburton OO sacks of cement. Cement circulated Stopped plug at 285', left 25' of  HOBBS OFFICE  L.H. Wents  Company of Operator By Position Send communications regarding well to Leigh Taliaferro
Set 13" O.D. 40# easing at 308' in the conting Company with 20 around 13" easing to top of hole.  Sement in casing. Total depth 335'	a shale, cemented by Halliburton  OO sacks of cement. Cement circulated  Stopped plug at 285', left 25' of  JUL 17 1939  HOBBS OFFICE  L.H. Wents  Company of Operator  By  L.M. J.