

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional

## instructions in the Rules and Regulations of the Commission. Indicate Nature of Report by Checking Below REPORT ON RESULT OF TEST REPORT ON BEGINNING REPORT ON REPAIRING WELL DRILLING OPERATIONS OF CASING SHUT-OFF X REPORT ON RESULT OF PLUGGING WELL REPORT ON RECOMPLETION REPORT ON **OPERATION** (Other) November 16, 1953 Hobbs, New Mexico Following is a report on the work done and the results obtained under the heading noted above at the Shell Oil Company Buckley "A" (Company or Operator) Bass Drilling Company 1/4 SW 1/4 of Sec. 25 T 14-S R 37-E NMPM Denton Pool, Lea The Dates of this work were as follows: Novembar 13, 1953 and approval of the proposed plan \*\* (was not) obtained. DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED Ran 12,266' of 52" casing and comented at 12,281' with 500 sacks 4% gel and 800 sacks neat cement. Did not circulate. Left 67' cement in casing. After WOC 8 hours ran temperature survey and found top of cement in annulus at 7450'. Stretch test indicated freeze point at 8690'. After WOC 56 hours tested casing and cement with 1500 psi for 30 minutes before and after drilling plug. Test OK. H. G. Starling Production Foreman Shell Oil Company (Company) I hereby certify that the information given above is true and complete Approved: OIL CONSERVATION COMMISSION to the best of my knowledge. Original signed by F. D. Leigh F. D. Leigh Name..... Division Mechanical Engineer Position ..... Shell Oil Company Representing NOV 18 1953

(Title)

Box 1957.

Address..

Hobbs, New Mexico