

N.

Orig: /

000
000 WBA
JTB
RDC(Revised 7/1/52)
(Form C-105)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

7 707 000

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLYSinclair Oil & Gas Company
(Company or Operator)Lee Whitman "A"
(Lease)Well No. **6**, in **SE** $\frac{1}{4}$ of **NE** $\frac{1}{4}$, of Sec. **26**, T. **14 S**, R. **37 E**, NMPM.

Denton Wolfcamp

Pool,

Lee

County.

Well is **2130** feet from **North** line and **660** feet from **East** lineof Section **26**. If State Land the Oil and Gas Lease No. isDrilling Commenced **4-1**, 19**54**. Drilling was Completed **5-19**, 19**54**.Name of Drilling Contractor **Frisbie & Yonney Drilling Company**Address **Tulsa, Oklahoma**Elevation above sea level at Top of Tubing Head **3012**. The information given is to be kept confidential until
19

OIL SANDS OR ZONES

No. 1, from **9296** to **9335** No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **None** to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	33.6	1	300	Larida			
9 5/8	26	1	4700	do			
7	26.23	1	9609	do			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/4	13 3/8	905	330	H. J. Samsters		
12 1/4	9 5/8	4709	2600	do		
8 3/4	7	9609	125	do		
	2	9337				

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized 4/2,000 Gal. 15% Mud acid, 3,000 Gal. of 15% Mud acid thru above perforations

Result of Production Stimulation **297 Bbl. per 24 hours on potential test.**

Depth Cleaned Out

9370

CORD OF DRILL-STEM AND SPECIAL TT

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 9410 feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing 6-1, 1954

OIL WELL: The production during the first 24 hours was 297 barrels of liquid of which 100 % was
was oil; _____ % was emulsion; _____ % water; and _____ % was sediment. A.P.I.
Gravity 39.6

GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
liquid Hydrocarbon. Shut in Pressure _____ lbs.

Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.	<u>2120</u>	T. Devonian	
T. Salt.	<u>2110</u>	T. Silurian	
B. Salt.		T. Montoya	
T. Yates	<u>3120</u>	T. Simpson	
T. 7 Rivers	<u>3170</u>	T. McKee	
T. Queen	<u>4102</u>	T. Ellenburger	
T. Grayburg	<u>4375</u>	T. Gr. Wash	
T. San Andres	<u>4504</u>	T. Granite	
T. Glorieta	<u>6190</u>	T.	
T. Drinkard <u>Clearfork</u>	<u>6704</u>	T.	
T. Tubbs	<u>7303</u>	T.	
T. Abo	<u>8014</u>	T.	
T. Helfcamp	<u>9317</u>	T.	
T. Miss.		T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	65	65	Caliche				
65	306	241	Caliche & Redbed				
306	1445	1139	Redbed				
1445	1819	374	Redbed & Shale				
1819	2171	352	Anhydrite, redbed & sand				
2171	2391	220	Anhydrite & Sand				
2391	2546	155	Anhydrite & Shale				
2546	3179	633	Anhydrite & salt				
3179	3703	524	Anhydrite & shale				
3703	4246	543	Anhydrite & Gyp				
4246	4406	160	Lime & Shale				
4406	4676	270	A anhydrite, Gyp & shale				
4676	4714	38	Lime & Shale				
4714	7029	2315	Lime				
7029	7122	93	Sandy lime				
7122	7907	845	Lime				
7907	8434	467	Sandy lime				
8434	9319	885	Lime & Shale				
9319	9346	27	Lime				
9346	9410	64	Sandy lime				
FTD	9370						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

August 10, 1954 (Date)
Company or Operator Sinclair Oil & Gas Company Address 520 East Broadway, Hobbs, New Mexico
Name GE. W. W. Position or Title Dist. Supt.