

Orig: & cc: OCC

(Form C-103)
(Revised 7/1/52)

cc: FB

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

TRIPPLICATE

MISCELLANEOUS REPORTS ON WELLS

HOBBS RECEIVED

1954 MAY 1 PM 3:22

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, or results of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 29, 1954

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

(Company or Operator)

Lee Whitman

(Lease)

Frisbie & Yancey Drlg. Co.

(Contractor)

Well No. 6 in the SE 1/4 NE 1/4 of Sec. 26

T 14 S, R 37 E, NMPM, Denton-Welfcamp Pool, Lea County.

The Dates of this work were as follows: 5-19-54

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 9410 - Set 7" O D casing @ 9409 and cemented with 125 sacks of cement. Ran temperature survey and found top of cement behind 7" O D casing @ 8615' from surface. Let cement set 72 hours, tested with 750 pounds pump pressure for 30 minutes before and after drilling cement plug.

PBTD 9370 - drilled cement plug to 9370, perforated W/4 Jet shots per foot from 9286 to 9306, 9310 to 9334 and 9347 to 9355.

Swabbed 19 barrels of oil in 2 hours. Acidized W/1,000 gallons of Mud acid, swabbed 227 Bbl. new oil in 24 hours. Acidized W/3,000 Gal. of 15% low tension. swabbed 280 Bbl. new oil in 24 hours.

Witnessed by H. W. Shaner

(Name)

Sinclair Oil & Gas Company

(Company)

Foreman

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name _____

Position Dist. Supt.

Representing Sinclair Oil & Gas Company

Address Box 1927 Hobbs, New Mexico

(Title)

(Date)