

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES

Nov 19 10 16 AM '63

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)November 18, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc.

T. D. Pope

Well No. 4 in M

(Company or Operator)

Lease

(Unit)

SW 1/4 SW 1/4 of Sec. 26, T. 14 S, R. 37 E, NMPM, Denton Devonian Pool

(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 12,640'

PB: 12,637'

Csg: 13 3/8" @ 409' w/425 ex., 9 5/8" @ 4,855' w/3,300 ex., 5 1/2" liner 4,639-12,640' w/2,100 ex.

Perfs: 12,305-12,361'; 12,446-12,488'; 12,500-12,526'; 12,539-12,594'.

Propose to move in and rig up unit. Drill & push pkr. to bottom w/bailer. Set retrievable pkr. @ 12,425'. Acidize perfs. 12,446-12,594' w/8,000 gals Dowell FLAX-2-N26 in 3 stages using 400 RCN ball sealers. Swab back acid water. Perf. 5 1/2" liner 12,189-12,225'; 12,244-12,299'; 12,363-12,395' w/1 JSPP. Set retrievable bridge plug @ 12,430'. Acidize perfs. 12,189-12,395' w/500 gals Mud Acid followed by 12,000 gals Dowell FLAX-2-N26 in 3 stages using 300 RCN ball sealers. Shut in 2 hrs. Swab test. If well flows shut in & measure BHP. If BHP is more than 1100# return to production. If BHP is less than 1100# remove bridge plug & return to production from all perfs.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Socony Mobil Oil Company, Inc.

Company or Operator

By.....

Position.....

Send Communications regarding well to:

Name Socony Mobil Oil Company, Inc.

Address Fox 1800, Hobbs, New Mexico

1997-1998