

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBBS OFFICE 000

MISCELLANEOUS NOTICES

1963 JUL 30 AM 10:13

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) Frac	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

July 29, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Secony Mobil Oil Company, Inc. **T. D. Pope** Well No. **24** in **0** (Unit)
(Company or Operator)
SE $\frac{1}{4}$ **SE** $\frac{1}{4}$ of Sec. **26**, T. **14S**, R. **37E**, NMPM., **Danton Wolfcamp** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 9390'
FB: 9388'
Csg: 10 3/4" @ 446 w/450 sx., 7 5/8" @ 4818' w/2191 sx., 5 1/2" liner 4668-9390' w/566 sx.
Perfs: 9225-9388'

Propose to kill well & pull tubing. Run Isotren log on 5" scale 8400-9388'. Perf. 5 1/2" liner 9120-9129, 9182-9186, 9372-9378 if log indicates oil and also perf. other possible pay zones as indicated by Isotren log. Run 3 1/2" tbg. & packer and frac. perfs. w/15,000 gal Acid-Kerosene Emulsion (85% Acid + 15% Kerosene) + 15,000# 20-40 Ottawa Sand in 3 stages. Drop 90 RCH ball sealers between each stage. Clean out sand w/bailer. Run artificial lift equipment, test and return to production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Secony Mobil Oil Company, Inc.

By.....
Position.....
Send Communications regarding well to:

Name.....
Address.....
Box 1800, Hobbs, New Mexico