

Orig: & cc: OCC
cc: FHR
JTR
F

(Form C-103)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) Perforating	<input checked="" type="checkbox"/>

September 20, 1954 Hobbs, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company W. T. Mann
(Company or Operator) (Lease)
A. W. Thompson Incorporated, Well No. 3 in the NW 1/4 NE 1/4 of Sec. 36
(Contractor)
T. 14 S, R. 37 E, NMPM, Denton (Devonian) Lea County.

The Dates of this work were as follows: Sept. 12, 15, 1954

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)
and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 12630, set 7" OD casing @ 12629 and cemented with 600 sacks of cement. Ran temperature survey which indicated top of cement behind 7" casing @ 8530' from surface. Let cement set 72 hours and tested casing with 1,000# pump pressure for 1 hour before and after drilling cement plug. Drilled cement plug to 12621.

PBTD 12621, perforated 7" OD casing with 4 - 1/2" jet shots per foot from 12462 to 12486, 12497 to 12509, 12522 to 12533 and 12588 to 12620.

Ran 12614' of 2" UE tubing and swabbed well in. Tested to tanks 414 barrels of clean oil in 10 hours thru 3/4" choke.

Witnessed by H. W. Shaner Sinclair Oil & Gas Company Foreman
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *W. T. Mann*

Position: Dist. Sup t.

Representing: Sinclair Oil & Gas Company

Address: 520 East Broadway, Hobbs, New Mexico

(Title)

(Date)