

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION
 Orig&2cc: OCC Hobbs, cc: Regional Office,
 cc: Partner, cc: file

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company	8. Farm or Lease Name W. T. Mann "A"
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico	9. Well No. 3
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>14S</u> RANGE <u>37E</u> NMP	10. Field and Pool, or Wildcat Denton Wolfcamp
11. Elevation (Show whether DF, RT, GR, etc.) 3801' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDON ☐
CASING TEST AND CEMENT JOBS ☐	
OTHER ☒ Plugback, Block Squeeze, perf. and test.	

17. Description of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting, if applicable.)

- 1-25-66 Set C.I. B. F. @ 12,345' w/3 sacks cement on top 12,330-12,345'. Jet perforated 7" casing @ 9502' w/4-1/2" holes for block squeeze.
- 1-28-66 Set Baker C.I. Retainer @ 9433'. Ran 2-7/8" tubing to retainer and block squeezed 7" casing thru perforations 9502' w/50 sacks Incor Max. Press. 3100#. KOC C. Mrs.
- 1-29-66 Tested perforations 9502' and casing to 1000# for 30 mins. Tested O.K. Jet perforated Wolfcamp 9284-88', 92', 94', 9299-9302', 9310-12', 9316-18', 9424-30', 9434-36' w/34 - 3/8" holes.
- 1-30-66 Acidized Wolfcamp perfs. 9284-9436' w/5000 gals. NE acid and 36 ball sealers. Max. Press. 4400#, Min. Press. 3300#, Inst. SIP 3500#, 10 mins. SIP 2250# @ 2.5 BPM.
- 2-2-66 Swabbed Wolfcamp perforations 9284-9436' 93 BNC plus 41 BAW in 10 hours. Recommended in Denton Wolfcamp and to be released to Mobil Oil Co. as operator of Denton Wolfcamp Unit after plugging back from Denton Devonian.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Superintendent DATE 2-3-66

APPROVE _____ TITLE _____ DATE _____

REMARKS OR COMMENTS OF APPROVAL, IF ANY: _____