

cc: [REDACTED]
[REDACTED]
[REDACTED]
[REDACTED]

Santa Fe, New Mexico

RECEIVED
AUG 27 1953
U. S. CONSERVATION COMMISSION
HOBBBS-OFFICE

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Sinclair Oil & Gas Company

(Company or Operator)

T. D. Pope

(Lease)

Well No. 2, in SE $\frac{1}{4}$ of S₃₄ $\frac{1}{4}$, of Sec. 36, T. 14 S, R. 37 E, NMPM.

_____ Denton _____ Pool, _____ Lea _____ County.

Well is 660 feet from South line and 1650 feet from West line

of Section 36-48-375 If State Land the Oil and Gas Lease No. is _____

Drilling Commenced 4-4, 19 53 Drilling was Completed 7-26, 19 53

Name of Drilling Contractor.....Coroco Drilling Company.....

Address..... Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head.....3800..... The information given is to be kept confidential until

....., 19.....

OIL SANDS OR ZONES

No. 1, from 12420 to 12650 No. 4, from _____ to _____

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from _____ to _____ feet.

No. 4, from.....to.....feet.

CASING RECORD

MUDDING AND CEMENTING RECORD

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized with 1,000 pellets of 7ad acid

.....

.....

Result of Production Stimulation..... flowed 60 bbl. of oil in one hour

Depth Cleaned Out.....12647

REPORT OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 12450 feet, and from feet to feet.
Cable tools were used from None feet to feet, and from feet to feet.

PRODUCTION

Put to Producing August 5, 1953

OIL WELL: The production during the first 24 hours was 1039 barrels of liquid of which 100% was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 45

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

T. Anhy.
T. Salt. 6240
B. Salt.
T. Yates.
T. 7 Rivers.
T. Queen.
T. Grayburg.
T. San Andres. 4660
T. Glorieta. 5200
T. Drinkard. 5830
T. Tubbs. 7353
T. Abo. 1050
T. Penn. Lime 9598
T. Miss. 11493

Northwestern New Mexico

T. Devonian. 12410
T. Silurian.
T. Montoya.
T. Simpson.
T. McKee.
T. Ellenburger.
T. Gr. Wash.
T. Granite.
T. Ojo Alamo.
T. Kirtland-Fruitland.
T. Farmington.
T. Pictured Cliffs.
T. Menefee.
T. Point Lookout.
T. Mancos.
T. Dakota.
T. Morrison.
T. Penn.
T.
T.
T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	75	75	Surface sand & Caliche	11579	11624	45	Lime
75	318	243	Caliche & Redbed	11624	11868	244	Lime & Chert
318	1895	1577	Redbed	11868	11921	53	Lime
1895	2080	185	Redbed & Shells	11921	11966	45	Lime & Shale
2080	2213	133	Redbed & Sand	11966	12034	68	Lime
2213	2474	261	Redbed & Shells	12034	12155	121	Lime & Shale
2474	3105	631	Redbed & Salt	12155	12157	2	Lime & Sand
3105	3275	170	Anhydrite & Salt	12157	12166	9	Lime & Shale
3275	4692	1417	Anhydrite	12166	12330	164	Lime
4692	5797	1105	Lime	12330	12363	33	Shale
5797	5983	186	Lime & Sand	12363	12382	19	Lime
5983	10961	4978	Lime	12382	12429	47	Lime & Shale
10961	10968	7	Lime & Sand	12429	12650	221	Lime
10968	11150	182	Lime				
11150	11173	23	Lime & Shale				
11173	11229	56	Lime				
11229	11243	14	Lime & Sand				
11243	11264	21	Lime				
11264	11275	11	Lime & Sand				
11275	11284	9	Lime				
11284	11332	48	Lime & Sand				
11332	11514	182	Lime & Shale				
11514	11535	21	Lime				
11535	11545	10	Lime & Shale				
11545	11579	34	Lime & Chert				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

August 7, 1953 (Date)
Company or Operator Sinclair Oil & Gas Company Address Box 1977 Hobbs, New Mexico
Name J. C. Miller Position or Title 1st. Asst.