

Orig: & cc: OCC

cc: VDA

JTR

(Form C-102)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 JUN 7 AM 7:50

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 4, 1954

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

(Company or Operator)

T. D. Pope

(Lease)

Frank Frawley Drlg. Company

(Contractor)

Well No. 10 in the SW 1/4 NW 1/4 of Sec. 36

T. 14 S, R. 37 E, NMPM, Denton-Wolfcamp Pool, Lea County.

The Dates of this work were as follows:

5-24-54

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan (was) (was not) obtained.

(Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 9370 - Set 7" casing @ 9369 and cemented with 125 sacks of cement. Ran temperature survey which indicated top of cement behind 7" casing at 8151 feet from surface. Let cement set 72 hours and tested casing with 750# pump pressure before and after drilling cement plug. Drilled cement plug to 9350.

PBTD 9350 - Perforated 7" casing W/4 - 1/2" jet shots per foot from 9194 to 9227, 9252 to 9260, 9280 to 9296, 9334 to 9346. Ran 9268' of 2 1/2" UE tubing W/Guiberson packer set @ 9138. Swabbed load water 19 hours, swabbed 52 Bbl. of new oil in 14 hours. Acidised W/1,000 Gal. of mud acid, 6,000 Gal. of 15% Low tension, swabbed 287 barrels of new oil in 24 hours.

Witnessed by: H. W. Shaner

(Name)

Sinclair Oil & Gas Co.

(Company)

Foreman

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: _____

Position: Dist. Supt.

Representing: Sinclair Oil & Gas Company

Address: Box 1927, Hobbs, New Mexico

Engineer District 1

(Title)

(Date)