

ATTACHMENT VI

WELL NAME	LOCATION	SPUD DATE	COMP DATE	WELL TYPE	DEPTH/PBTD	COMPLETION RECORD
State T #3	1980' FSL & 1980' FWL Sec. 2-15S-37E Lea County, NM	1/13/52	6/22/52	Oil	12,483'	13 3/8" csg @ 343' w/350 sxs cmt. Circ'd cmt.
						9 5/8" csg @ 4625' w/3000 sxs cmt. TOC @ 1160' (temp survey).
						7" csg @ 11,715' w/800 sxs cmt. TOC @ 9157'.
						Open hole completion 11,715'-12,483'.
						5" liner @ 11,554'-12,482' w/125 sxs cmt. Est. TOC top of liner (calc). Perfd 11,725'-12,294'.
State T #4	660' FSL & 660' FWL Sec. 2-15S-37E Lea County, NM	4/6/52	8/29/52	Oil	12,400'/12,395'	13 3/8" csg @ 327' w/325 sxs cmt. Circ'd cmt.
						9 5/8" csg @ 4663' w/3000 sxs cmt. Circ'd cmt.
						7" csg @ 12,400' w/465 sxs cmt. TOC @ 8330' (temp survey).
						Perfd 12,257'-12,393'
						Perfd 12,100'-12,216'
						CIBP @ 12,230' w/1 sx cmt on top.
						Squeezed perfs 12,100'-12,216' w/29 sxs cmt.
						Perfd 11,990'-11,991', set cmt ret @ 11,970', & squeezed w/30 sxs cmt.
						Perfd 11,900'-11,954'.
						Squeezed perfs 11,900'-11,954' w/75 sxs cmt. Cmt ret @ 11,852' w/40 sxs cmt. on top. Perfd 8315'-8317'. Cmt plug 8361'-8496'.
			10/6/80	P&A'd	12,400'/surf.	Perfd 4668'-4670'. Set cmt retainer @ 4610', squeezed 580 sxs cmt in washout below 4668' & spotted 20 sxs cmt on cmt retainer.
						Spotted 21 sxs cmt 2150'-2280'. Spotted 10 sxs cmt @ 60'.
						Installed dry hole marker. P&A'd
						Re-entered wellbore. Perfd 11,667'-12,204'.
			9/22/93	Oil	12,400'/12,224'	

1