

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)December 28, 1956
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation Lea State "G" Well No. 6-wo in J
(Company or Operator) (Unit)
NW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 2, T. 15-S, R. 37-E, NMPM., Denton-Wolfcamp Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to ~~squeeze cement, perforate and acid treat~~ as follows:

1. Pull tubing.
2. Run tubing with cement retainer set at approximately 8975'. Squeeze cement perforated interval from 9050-9085'. Pull tubing. WOC.
3. Run 2-7/8" tubing and bit, drill out to 9155'. Run Gamma Ray Neutron.
4. Perforate 7" casing from 9100-9150' with 4, 1/2" jet holes per foot.
5. Set Baker Model D production packer on electric line at 9095'. Run 2-7/8" tubing, seal nipple and engage packer. Swab and test. If warranted acid treat with 2000 gallons 15% acid.

Approved..... 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy E. J. Fischer
Title.....Gulf Oil Corporation
Company or OperatorBy E. J. Fischer
Position Area Supt. of Prod.
Send Communications regarding well to:Name Gulf Oil Corporation
Address Box 2167, Hobbs, New Mexico