NEW MEXICO OIL CONSERVATION COMMISSION

## ISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work so is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, result of casing shut off, result of plugging of well, and other important operations, even though the work was reflected by agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate nature of report by checking below.

| REPORT ON BEGINNING DRILLING<br>OPERATIONS                    | REPORT ON REPAIRING WELL                       |
|---|--|
| REPORT ON RESULT OF SHOOTING OR<br>CHEMICAL TREATMENT OF WELL | REPORT ON PULLING OR OTHERWISE ALTERING CASING |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF                   | REPORT ON DEEPENING WELL                       |
| REPORT ON RESULT OF PLUGGING OF WELL                          |  |

|                                 |                    | May 14, 1951<br>Date |                | Hobbs, Hen Hexi co |                |        |        |
|---------------------------------|--------------------|----------------------|----------------|--------------------|----------------|--------|--------|
| Following is a report on the wo | ork done and the r | esults obtain        | ed under the l | heading not        | ted above at t | the    |        |
| Skelly Oil Company              |                    | <b>}</b>             | Mexico "F"     |                    |                | in the | in the |
| NE/4 NW/4                       | or Operator        |                      | Lease          | e                  |                |        |        |
| Denton                          |                    |                      |                |                    |                |        |        |
| The dates of this work were as  | follows:           |                      | May 13,        | 1951               |                |        |        |
| Notice of intention to do the w | ork was (          | ) submitted (        | on Form C-10   | 2 on               | May 11         |        |        |
| and approval of the proposed p  | lan was (was not)  | obtained. (C         | ross out incor | rect words.        | .)             |        |        |
| DET                             | AILED ACCOUNT      | r of work            | DONE AN        | D RESULT           | IS OBTAIN      | ED     |        |

Drilled to total depth of 12,887. Ran 5-1/2" OD casing to 12,887, and cemented with 1500 sacks in two stages, using Halliburton process. Cemented with 780 sacks in first stage and circulated out excess cement above Halliburton DV tool set at 8923. Waited 6 hours and cemented with 720 sacks through Halliburton DV tool. Temperature survey showed top of cement on second stage at 4695. Let set 72 hours and on May 13, 1951, at approximately 7:50 P.M. drilled plug and tested casing shut-off. Shut-off tested OK.

| Witnessed by S. E. R. Deitz           | Skelly Oil Company Forman Title   |
|---------------------------------------|---|
| APPROVED: OIL CONSERVATION COMMISSION | I hereby swear or affirm that the information given above is true and correct                               |
| MAY 16 1951 19                        | Position Dist. Supt.  Representing Skelly Oil Company Company or Operator  Address Drawer "D", Hobbs, N. M. |

1. M. J. 202 Dillows

•