

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<b>XX</b>	NOTICE OF INTENTION TO ACIDIZE	<b>XX</b>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<b>XX</b>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

January 9, 1963  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Mexico "F"

Shelly Oil Company  
(Company or Operator)

Well No. 4 in "D"  
(Unit)

SW 1/4 NW 1/4 of Sec. 2, T. 15-S, R. 37-E, NMPM., Denton Pool  
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Move in and rig up workover rig.
2. Pull pump and tubing.
3. Mill out Baker Model "D" Production Packer set at 12,228'.
4. Set Howe "EC" Cement Retainer at approximately 12,224'.
5. Squeeze open hole section with 200 sacks of cement.
6. Drill out retainer and cement to approximately 12,414'.
7. Treat open hole section with 500 gallons Mud Acid.  
If the open hole section is non productive will proceed as follows:
8. Set Retrivable Bridge Plug at approximately 12,250'.
9. Selective perforate from approximately 12,168' to 12,217'.
10. Treat perforations with 500 gallons Mud Acid.
11. Pull Retrivable Bridge Plug.
12. Set Baker Model "D" Production Packer at approximately 12,150'.
13. Run tubing and hydraulic pump.
14. Return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Shelly Oil Company

Company or Operator  
(ORIGINAL) H. E. Asb

By.....

Position..... Dist. Supt.

Send Communications regarding well to:

Name..... Shelly Oil Company

Address..... Box 38 - Hobbs, New Mexico

