

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|-------------------------------------|--|--|---|--|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO PLUG BACK | | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)September 18, 1961
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation (Company or Operator) W. A. Simpson et al Tr. "B" Well No. 2 in J (Unit)
 NW 1/4 SE 1/4 of Sec. 3, T. 15-S, R. 37-E, NMPM., Denton Wolfcamp Pool
 (40-acre Subdivision)
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 12,700'. FBTD 12,289'. It is proposed to plug & abandon as follows:

1. Recover pump & pull tubing.
2. Shoot 7" casing off at approximately 8325' and 9-5/8" at approximately 1100' and recover all casing and well head equipment.
3. Lead hole with mud and spot cement plugs as follows:
 9395-9240' (across Wolfcamp perforations)
 From 50' below 7" casing stub to 50' above 7" casing stub.
 From 7450-7350' (across Tubb)
 From 6220-6120' (across Glorietta)
 From 4770-4670' (across 9-5/8" casing shoe)
 From 50' below 9-5/8" casing stub to 50' above 9-5/8" casing stub.
 From 415-315' (across 13-3/8" casing shoe)
 From 50' to surface.
4. Install 4" x 4" surface marker, salvage all surface equipment and clean location. Salvage all equipment on lease, clean and abandon lease.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....Gulf Oil Corporation
Company or Operator

By.....

Position..... Area Production Manager
Send Communications regarding well to:

Name..... Gulf Oil Corporation

Address..... Box 2167, Hobbs, New Mexico

