

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-183
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Denver DD, Aztec, NM 88210

DISTRICT III
1000 Rio Blanco Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-05263
5. Indicate Type of Lease	STATE ☐ PER ☒
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Argo
8. Well No.	2
9. Foot name or Wildcat	Denton Devonian

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL ☒ GAS ☐ OTHER ☐	2. Name of Operator Polaris Production Corp.
3. Address of Operator P. O. Box 1749, Midland, TX 79702	4. Well Location Unit Letter H : 2287 Feet From The North Line and 330 Feet From The East Line Section 3 Township 15-S Range 37-E 4 NMPM Lea County
10. Elevation (Show whether DP, RKB, RT, GR, etc.) 3820 DF	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐		CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: ☐	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-13-97 Set CIBP @ 11,980 and spot 5 sx cement on top. TOC 11,938.
11-17-97 Pulled 2890' of 5 1/2" csg.
11-17-97 Spot 25 sx cement 9000'-8760'.
11-17-97 Spot 25 sx cement 6000'-5760'.
11-18-97 Spot 25 sx cement 4850'-4610'. Tagged TOC. Perf and could not pump into perfs.
11-19-97 Spot 50 sx 3050'-2730'. Tagged TOC. Approved as to plugging of the Well Bore.
11-20-97 Spot 35 sx 2200'-2076'. Liability under bond is retained until
11-20-97 Spot 35 sx 390'-256'. surface restoration is completed.
11-20-97 Spot 10 sx @ 30' to surface.
Circulate 10# mud between plugs and Install Dry Hole Marker.

I hereby certify that the information shown is true and complete to the best of my knowledge and belief.

SIGNATURE Davis Payne TITLE President DATE 12-28-97

TYPE OR PRINT NAME Davis Payne TELEPHONE NO. 915/684-8248

(This space for State Use)

APPROVED BY GWW TITLE FIELD REPRESENTATIVE II/STAFF MANAGER DATE JAN 16 2003

CONDITIONS OF APPROVAL: WINK

TO GWW