NO. OF COPIES RECEIVED		₩.z	70-C122 -
			Form C-103
DISTRIBUTION		la de la companya de	Form C-103 Supersedes Old 050 13 C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSER	YATION COMMISSION	Effective 1-1-65
FILE		U. G. G.	
U.S.G.S.	for 21	ŕ	5a. Indicate Type of Lease
LAND OFFICE	U44 3 1	δ 32 AH '66	State Fee X
OPERATOR			5. State Oil & Gas Lease No.
			5. State Off & Gas Lease No.
(DO NOT USE THIS FORM	UNDRY NOTICES AND REPORTS ON WE FOR PROPOSALS TO BRILL OR TO DEEPEN OR PLUG BACK PLICATION FOR PERMIT —" (FORM C-101) FOR SUCH P	ELLS	
USE 44A	PLICATION FOR PERMIT - " (FORM C-101) FOR SUCH P	TO A DIFFERENT RESERVOIR. Roposals.)	
14.			7. Unit Agreement Name
OIL X GAS WELL	OTHER-		1
2. Name of Operator			8. Farm or Lease Name
No Al	actor Fuel Common	38993	16.1 dail of Ledise Name
3. Address of Operator	ester Fuel Company (30	I. M. Denton A 16195 9. Well No.
			9. Well No.
P. O.	Box 210, Magnolia, Arkansas 717	753	★ -1
4. Location of Well			10. Field and Pool, or Wildcat/12 9
UNIT LETTER 0	660 FEET FROM THE South	1.980	Donton Doy & Walfarma
SWIT EETTEN	FEET FROM THE	LINE AND 11700 PEET FROM	Denton Dev. & Wolfcamp
Fact	11 150	272	
THE LAST LINE	SECTION 11 TOWNSHIP 15S	RANGE 3/E NMPM.	
mmmmmm			
	15. Elevation (Show whether DF,	, RT, GR, etc.)	12. County
	3,799' D,F.		Lea
16.		and a final and a	
Va=10=	eck Appropriate Box To Indicate Natu		
NOTICE	OF INTENTION TO:	SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON RE	EMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		OMMENCE DRILLING OPNS.	
PULL OR ALTER CASING		 	PLUG AND ABANDONMENT
	CHANGE PLANS	ASING TEST AND CEMENT JOB	
		OTHER	
OTHER	——————————————————————————————————————		
17 Describe Described on Comple	ted County (CL 1 in the county)		
work) SEE RULE 1103.	ted Operations (Clearly state all pertinent details,	and give pertinent dates, including	estimated date of starting any proposed
Diagod 25 made		0 5001	
Attaced 25 sack (ement plug inside 5-1/2" casing f	rom 9,500° to 9,290°.	
Attempted to sn	oot off casing at 7,285' - Failed.		•
Shot casing at 5	777' but could not pull.		
Shot casing at 2	993' and recovered 5-1/2" casing	r	
Placed 25 sack cement plug in stub from 3,025'.			
Set 10 sack cement plug in top of 9-5/8" casing.			
Erected surface	monument.		
18. I hereby certify that the infor-	nation above is true and complete to the best of my	In-	
	above to true and complete to the best of my	knowledge and belief.	
<i>n n</i>	φ		
SIGNED .	hauf the Ch	ief Engineer	January 28 1066
SIGNED A.A.	Lary TITLE Ch	ief Engineer	DATE January 28, 1966
SIGNED . A.	Kary TITLE Ch	ief Engineer	DATE January 28, 1966
SIGNED A.A.	Kary TITLE Ch	ief Engineer	DATE January 28, 1966
APPROVED BY	Kary TITLE Ch	ief Engineer	January 28, 1966
APPROVED BY John	M. Kunyau TITLE Ch.	ief Engineer	January 28, 1966