

APPLICATION FOR AUTHORITY TO INJECT
Supplemental Information
(Continued)
J. M. DENTON WELL NO. 5
Lea County, New Mexico

Operator: McAlester Fuel Company

Well Name: Denton "A" Well No. 1

Location: 660' FSL & 1980' FEL, (0) Sec. 11, T15S, R37E

Spud Date: March 14, 1949

Surface Casing: 13 3/8" set at 350', cemented with 500 sx.

Intermediate Casing: 9 5/8" set at 4655', cemented with 1500 sx.

Production Casing: 5 1/2" set at 11,465', cemented with 1100 sx.

Completion: Originally completed in the Devonian from 11,325-464'.
Plugged back to 9536' and perforated Wolfcamp from 9490-9530'.
P&A in 1966 (see attached schematic).

Operator: Lynx Petroleum Consultants

Well Name: Pat H. McClure "C" Well No. 1

Location: 330' FNL & 990' FEL, (A) Section 14, T15S, R37E

Spud Date: March 13, 1951

Surface Casing: 13 3/8" set at 338', cemented with 400 sx.

Intermediate Casing: 9 5/8" set at 4740', cemented with 2078 sx.

Production Casing: 5 1/2" set at 12,750', cemented with 1000 sx.

Completion: Originally completed in the Devonian from 12,650-737'.
Plugged back to 9210'. Completed in the Wolfcamp from
9082-9181'. Squeezed. Added perms from 9147-9181'.

TFZ/76/dah