

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED

MAR 22 1951

OIL CONSERVATION COMMISSION  
HOPE'S OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

3-19-51

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Phillips Petroleum Company Denton Well No. 1 in the  
Company or Operator Lease  
SE 1/4 NW 1/4 of Sec. 11, T. 15-S, R. 37-E, N. M. P. M.,  
Denton Field, Lea County.

The dates of this work were as follows: 3-15 & 16 - 51

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on 3-19-51 19\_\_\_\_  
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

T.D. 12,623. Ran 324 joints, 12,610' of 5-1/2" casing set at 12,621'. Cemented in two stages. 1st stage with 548 sacks 4% Slogel mixed with 238 sacks grade B&C Wellite followed by 50 sacks common. Pumped plug to 12,581'. Second stage, cemented with 1100 sacks 4% gel. Pumped plug to 8870. Cement circulated to surface. Tested OK before and after drilling plug.

Witnessed by D. M. Barton Phillips Petroleum Foreman  
Name Company Title

Subscribed and sworn before me this

19 day of March 19 51

*[Signature]*  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name W. G. Lawton

Position District Chief Clerk

Representing Phillips Petroleum Company  
Company or Operator

My commission expires My Commission Expires November 30, 1954

Address Box 1605 Hobbs, New Mexico

Remarks:

APPROVED

Date MAR 22 1951

*[Signature]*  
Name  
Oil & Gas Inspector  
Title

