

## NL MEXICO OIL CONSERVATION COL .ISSION

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within is completed. It should be signed and filed as a report on beginning drilling operations, result of casing shut off, result of plugging of well, and other important operations, even though agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

he work OBB STORMS by an

	Indicate nature of	report by checking be	iow.	
REPORT ON BEGINNING DRIP	LING	REPORT ON	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHER ALTERING CASING		;
REPORT ON RESULT OF TEST	OF CASING	REPORT ON	DEEPENING WELL	
REPORT ON RESULT OF PLUC				
		1-18-52 Date	Hobbs, Ner	r Mexico
Following is a report on the work			noted above at the	
Company or	Operator of Sec. 11	Lease T. 155	, R	, N. M. P. M.,
•				
he dates of this work were as fo	1.4	.53		
otice of intention to do the work				
Well spudded ll:	LED ACCOUNT OF WOF 00 A.M. 1-5-52 348'. ran 9 joints	k done and rest	S* OD casing set at	
Well spudded ll:0 Drilled well to 3 346.39'. Cement 280'. Cement oil drilling plug.	LED ACCOUNT OF WOF 20 A.M. 1-5-52 348', ran 9 joints and with 350 sacks realated to surface rest OK.	, 336' of 13-3/regular coment.  Tosted casi	8° OD casing set at Pumped plug te ng before and after	
Well spudded ll:0 Drilled well to 3 346.39'. Cement of 280'. Cement of drilling plug.	LED ACCOUNT OF WOF 30 A.M. 1-5-52 348', ran 9 joints ad with 350 sacks realated to surface rest OK.	, 336' of 13-3/regular coment.  Tested casi	8* OD casing set at Pumped plug to ng before and after	Title
Well spudded ll:0 Drilled well to 346.39'. Cement 280'. Cement did drilling plug.	LED ACCOUNT OF WOF  OO A.M. 1-5-52  348', ran 9 joints and with 350 sacks realated to surface  Test OK.	, 336' of 13-3/regular coment.  Tested casi	8* OD casing set at Pumped plug to ng before and after  or affirm that the informatio ect.	Title
Well spudded list Drilled well to 3 346.39'. Cement cir 280'. Cement cir drilling plug.	Underwood Name  Name	, 336' of 13-3/regular coment.  Tosted casi  Company  I hereby swear	S* OD casing set at Pumped plug te ng before and after  or affirm that the informatio	Title
Well spudded list Drilled well to 346.39'. Cement 280'. Cement cir drilling plug.  Witnessed by D. C.	Underwood Name  Name  Name  Name	Phillips Per Company  I hereby swear is true and corr	8° OD casing set at Pumped plug te ng before and after  or affirm that the informatio ect.  Dist. Chief Clerk	n given above
Well spudded 11:0 Drilled well to 346.39'. Cement air 280'. Cement air drilling plug.  Witnessed by D. C.	Underwood Name  Name	Phillips Per Company  I hereby swear is true and corr	8° OD casing set at Pumped plug te ng before and after  or affirm that the informatio ect.  Wildron to.  Dist. Chief Clerk	n given above