

NEW MEXICO

ON COMMISSION

Santa Fe, New Mexico

WELL RECORD

RECEIVED

OIL CONSERVATION COMMISSION
OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico. Proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Phillips Petroleum Company **Denton**
Company or Operator Lease
Well No. **6** in **NE/4NW/4** of Sec. **11**, T. **15S**
R. **37E**, N. M. P. M., **Denton** Field, **Lea** County.
Well is **659** feet south of the North line and **1987** feet **east** of the **East** line of **N/2 Sec. 11**
If State land the oil and gas lease is No. _____ Assignment No. _____
If patented land the owner is **James M. Denton**, Address **Brownfield, Texas**
If Government land the permittee is _____, Address _____
The Lessee is **Phillips Petroleum Company**, Address **Bartlesville, Oklahoma**
Drilling commenced **December 21** 19 **51**. Drilling was completed **May 31** 19 **52**
Name of drilling contractor **Corbett Drilling Company**, Address **Tulsa, Oklahoma**
Elevation above sea level at top of casing **3797** feet.
The information given is to be kept confidential until **Not confidential** 19 _____

OIL SANDS OR ZONES

No. 1, from **12,500** to **12,600** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **NR** to _____ feet. _____
No. 2, from _____ to _____ feet. _____
No. 3, from _____ to _____ feet. _____
No. 4, from _____ to _____ feet. _____

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
13-3/8	27.3#	Slip Jt.	Sals	338'	None				Surface
8-5/8	24# & 32#	8rd	Sals	4640'	Hawco				Salt String
5-1/2	15.5, 17, 20	8rd	Sals	12685'	Bakar				Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2	13-3/8	349	450	Halliburton		
11	8-5/8	4650	1725	Halliburton		
7-7/8	5-1/2	12695	1435	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Western Co.	1000 gals.	6-5-52	12,500-600	

Results of shooting or chemical treatment **Flowed 12 hrs., 1/2" choke, 460 bbls. oil, Gravity 45, GOR 833**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **12,700** feet, and from _____ feet to _____ feet.
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing **June 5** 19 **52**
The production of the first 24 hours was **920** barrels of fluid of which **99.7** % was oil; _____ %
emulsion; _____ % water; and **.3** % sediment. Gravity, Be **45**
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Driller _____ Driller _____
Driller _____ Driller _____

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Hobbs, New Mexico

June 17, 1952

Name **W. Hobbs**

Position **District Chief**

Representing **Phillips**

Company or Operator.

Address **Box 2105,**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	350		Surface & Red Bed
350	1826		Red Bed
1826	1990		Red Bed & Anhydrite
1990	2163		Anhydrite
2163	2330		Anhydrite & Salt
2330	2695		Salt
2695	3427		Salt & Anhydrite
3427	4569		Anhydrite & Gyp
4569	4650		Anhydrite & Lime
4650	9404		Lime
9404	9450		Lime & Shale
9450	10,465		Lime
10,465	10,502		Lime & Chert
10,502	10,690		Lime
10,690	10,761		Lime & Shale
10,761	10,953		Lime & Chert
10,953	11,006		Lime & Shale
11,006	11,054		Lime
11,054	11,250		Lime & Shale
11,250	11,421		Lime
11,421	11,572		Lime & Shale
11,572	12,700		Lime