

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED

MAY 1 1952

OIL CONSERVATION COMMISSION
HOBBS OFFICE

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Phillips Petroleum Company

Denton

Well No. 10 in NE/4 NE/4 of Sec. 11, T. 15S

R. 37E, N. M. P. M., Denton Wolfcamp Field, Lea County.

Well is 658 feet North of the South line and 562 feet west of the East line of NE/4 Sec. 11-15-37

If State land the oil and gas lease is No. --- Assignment No. ---

If patented land the owner is James M. Denton, Address Brownfield, Texas

If Government land the permittee is ---, Address ---

The Lessee is Phillips Petroleum Company, Address Bartlesville, Oklahoma

Drilling commenced January 27, 1952 Drilling was completed March 26, 1952

Name of drilling contractor Phillips Petroleum Company, Address Bartlesville, Oklahoma

Elevation above sea level at top of casing 3,790 feet.

The information given is to be kept confidential until Not confidential, 19---

OIL SANDS OR ZONES

No. 1, from 9167 to 9435 No. 4, from --- to ---

No. 2, from --- to --- No. 5, from --- to ---

No. 3, from --- to --- No. 6, from --- to ---

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from NR to --- feet.

No. 2, from --- to --- feet.

No. 3, from --- to --- feet.

No. 4, from --- to --- feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13-3/8"	27.3#	Slip Jt.	Sals.	341	None			Surface
8-5/8"	32# & 24#	8rd	Sals.	4639	Howco			Salt String
5-1/2"	15.5# & 17#	8rd	Sals.	9601	Baker			Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8"	351'	390	Halliburton		
11"	8-5/8"	4649'	2400	Halliburton		
7-7/8"	5-1/2"	9611'	925	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material --- Length --- Depth Set ---

Adapters—Material --- Size ---

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Western Co.	1000 gal.	4-24-52	9285-9415	

Results of shooting or chemical treatment Flowed 14 hrs., 1/2" choke, 210 bbls. oil, no water, Gravity 42.6, GOR 364.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 9614 feet, and from --- feet to --- feet.

Cable tools were used from --- feet to --- feet, and from --- feet to --- feet.

PRODUCTION

Put to producing April 24, 1952

The production of the first 24 hours was 390 barrels of fluid of which 99.7 % was oil; --- %

emulsion: --- % water; and 3 % sediment. Gravity, Be 43

If gas well, cu. ft. per 24 hours --- Gallons gasoline per 1,000 cu. ft. of gas ---

Rock pressure, lbs. per sq. in. ---

EMPLOYEES

Driller --- Driller ---

Driller --- Driller ---

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Hobbs, New Mexico

April 30, 1952

Place

Date

Name

H. E. Gorton

Position

District Chief Clerk

Representing

Phillips Petroleum Company

Company or Operator.

Address

Box 2105, Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	351		Caliche & Red Bed
351	2012		Red Bed and Red Rock
2012	2100		Red Bed & Sand
2100	2400		Anhydrite
2400	3431		Anhydrite & Salt
3431	3540		Anhydrite, Gyp and Sand
3540	3728		Anhydrite, Gyp & Salt
3728	3822		Anhydrite & Salt
3822	4258		Anhydrite & Gyp
4258	4376		Anhydrite, Gyp & Lime
4376	4424		Anhydrite & Gyp
4424	4551		Anhydrite
4551	4624		Anhydrite & Lime
4624	8838		Lime
8838	8875		Lime & Shale
8875	9614		Lime

DUPLICATE