
NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF INTENTION TO SHOO CHEMICALLY TREAT WELL	T OR
OTICE OF INTENTION TO CHANGE PLANS	-	NOTICE OF INTENTION TO PULL OTHERWISE ALTER CASING	OR
OTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG	WELL
OTICE OF INTENTION TO DEEPEN WELL			
	N.	dland, Taxas December	er 27. 19k9
IL CONSERVATION COMMISSION, anta Fe, New Mexico.		Place Da	te
Sentlemen:			
ollowing is a notice of intention to do certain wo			
Company Bettie C. Dickir Company or Operator Le	ase	Well No. 1	in SW/4
Sec. 12 , T. 15-8 , R. 37-8	, N	I. M. P. M., Denton	Field
County.			
FULL DETAILS OF	PROF	OSED PLAN OF WORK	
fter drilling to 4607 feet, 119 joi -55, easing was rum and comented at iroulated to the surface. The plus ours for the coment to harden, the	ints o t 4606 z was	In new 9-5/8" O.D., 36f and 40 with 3,000 sacks of cement. down at 4:15 AM 12-25-49. At	H-40 and The sement ter waiting
ifter drilling to 4607 feet, 119 joi 1-55, easing was rum and cemented at sirculated to the surface. The plug sours for the cement to harden, the sinutes.	ints o t 4606 z was	IND REGULATIONS OF THE COMM of new 9-5/8* 0.D., 36# and 40 with 3,000 sacks of cement. down at 4:15 AM 12-25-49. An ag will be tested with 1000# p	H-40 and The cement ter waiting areasure for
Ifter drilling to 4607 feet, 119 joid 1-55, casing was run and cemented at airculated to the surface. The plug sours for the cement to harden, the sinutes.	ints o t 4606 z was	In new 9-5/8" O.D., 36f and 40 with 3,000 sacks of cement. down at 4:15 AM 12-25-49. At	H-40 and The cement ter waiting l pressure for
fter drilling to 4607 feet, 119 joi 55, casing was run and comented at iroulated to the surface. The plugours for the cement to harden, the inutes.	ints o t 4606 z was	The Atlantic Refining Comp	H-40 and The cement ter waiting l pressure for
Ifter drilling to 4607 feet, 119 joing 1-55, casing was run and cemented at airculated to the surface. The plug sours for the cement to harden, the sinutes.	ints o t 4606 z was	The Atlantic Refining Company or Operator	H-40 and The cement ter waiting pressure for Calley ha
ifter drilling to 4607 feet, 119 joi y-55, casing was run and cemented at airculated to the surface. The plug nours for the cement to harden, the ainutes.	ints o t 4606 z was	The Atlantic Refining Company or Operate By	The cement ter waiting pressure for pressure for pressure for
oproved cept as follows:	ints o t 4606 z was	The Atlantic Refining Company or Operate By J. E. Hellinghausen Position Division Drilling Sy Send communications regarding	The cement ter waiting pressure for pressure for Cally ha

n de la companya de l

er de la companya de la co

And the second s