

HONDO OIL AND GAS COMPANY
APPLICATION FOR AUTHORITY TO INJECT
B. C. DICKINSON "B" WELL NO. 5
PAGE 6

Operator: Lynx Petroleum Consultants

Well Name: Pat H. McClure "C" Well No. 1

Location: 330' FNL & 990' FEL, (A) Section 14, T15S, R37E

Spud Date: March 13, 1951

Surface Casing: 13 3/8" set @ 338', cemented with 400 sxs.

Intermediate Casing: 9 5/8" set @ 4740', cemented with
2078 sxs.

Production Casing: 5 1/2" set @ 12,750', cemented with
1000 sxs.

Completion: Originally completed in the Devonian from
12,650'-12,737'. Plugged back to 9210'.
Completed in the Wolfcamp from 9082'-9181'.
Squeezed perfs, added perfs from 9147'-9181'.

Operator: Marathon Oil Company

Well Name: J. M. Denton Well No. 3

Location: 1980' FSL & 1980' FEL, (J) Section 11, T15S, R37E

Spud Date: August 25, 1950

Surface Casing: 13 3/8" set @ 371', cemented with 350 sxs.

Intermediate Casing: 9 5/8" set @ 4749', cemented with
2000 sxs.

Production Casing: 5 1/2" set @ 12,117', cemented with
1807 sxs.

Completion: Completed in the Devonian from
11,916'-12,044'.