

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

DUPLICATE  
(Form C-103)  
(2-7-1954 7-11-75)  
HOBBS OFFICE DEC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) <b>Conversion to SMD Well</b>	X	NOTICE OF INTENTION (OTHER) <b>S-H Free</b>	X

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Denver City, Texas  
(Place)

April 10, 1958  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**The Atlantic Refining Company** (Company or Operator) **B. C. Dickinson** "A-13" Well No. **1** in **D** (Unit)  
1/4 (40-acre Subdivision) 1/4 of Sec. **35**, T. **24-N**, R. **37-E**, NMPM, **Denton (Wolfcamp)** Pool  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

The following is a proposed plan for the conversion of our B. C. Dickinson "A-13" Well #1 in the Denton (Wolfcamp) Field. Pull the present installation, rods, tubing, pump etc., from the well. Pick-up Baker 7" full bore cement retainer and test cement plug @ 9424'. If plug holds pick-up retainer to 9320' and squeeze present perforations @ 9330'-9380' with 200 sac. cement. Pull retainer out and go-in with 3 7/8" bit and six 3" drill collars. Drill out cement to 9424' and bradenhead test (2000') squeezed perforations and liner-hanger. If tests prove satisfactory, cement cleaning out to 12,754'. Set 5" -18# Model E cast iron retainer @ 12,000' with 2 sac of cement on top of retainer. Perforate 9985' to 10,010' with 6 jet shots 7 ft. Acidize these perforations with 4000 gals. Then if necessary fracture perforations 9985'-10,010' w/5,000 gallons of water and 5,000# sand. Complete for SMD without tubing. Following the completion of Conversion operations, a form C-103, Miscellaneous Reports on Wells, will be submitted showing results of and status of well. April 21, 1958, is the proposed date for the start of above operations.

Ref: Order No. SMD #5 dated 9-10-57 from Mr. A. L. Porter, Jr.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....  
Engineer District 1

THE ATLANTIC REFINING COMPANY  
Company or Operator

By.....  
Position.....  
Send Communications regarding well to:

Name.....  
Address.....