NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the rules and Regulations of

| Indicate nature of notice by checking below: | |
|--|---|
| Indicate nature of n | otice by checking below: |
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL |
| NOTICE OF INTENTION TO CHANGE PLANS | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |
| NOTICE OF INTENTION TO REPAIR WELL | NOTICE OF INTENTION TO PLUG WELL |
| NOTICE OF INTENTION TO DEEPEN WELL | |
| He | ebbs, New Mexico May 26, 1942 |
| | Place Date |
| OIL CONSERVATION COMMISSION, Santa Fe, New Mexico | |
| Gentlemen: | |
| Following is a notice of intention to do certain work as de | escribed below at the |
| Gulf Oil Corporation L. R. Chamber Company or Operator Lease | rlain Well No. 5 in NW NE |
| · · · · · · · · · · · · · · · · · · · | , N. M. P. M., Denton-Wolfcamp Field |
| Lea County. | Field |
| - | |
| PILL HELALISTIN PRI | ODOCED DY ANY OR TYPODES |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with | OPOSED PLAN OF WORK S AND REGULATIONS OF THE COMMISSION 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job compl | 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented enghorn and Portland cement. Plug at |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job compl | 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented enghorn and Portland cement. Plug at leted by HOWCO 11:30 PM 5-23-52. |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job complements of the complement of the complement of the complement of the complements of the complem | 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented enghorn and Portland cement. Plug at leted by HOWCO 11:30 PM 5-23-52. casing shut-off 11:30 AM 5-25-52. |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job complements of the complement of the complement of the complements of the comple | 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented enghorn and Portland cement. Plug at leted by HOWCO 11:30 PM 5-23-52. |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job complements of the complement of the complement of the complement of the complements of the complem | 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented onghorn and Portland cement. Plug at leted by HOWCO 11:30 PM 5-23-52. Casing shut-off 11:30 AM 5-25-52. |
| On May 23, 1952 ran 9 joints, 28 H-40 R-2 ST&C National SS casing with at 300.73' w/350 sacks regular neat Le 280'. Cement circulated OK. Job complements of the complement of the complement of the complement of the complements of the complem | SAND REGULATIONS OF THE COMMISSION 86.73' of 13-3/8" OD 8 Rnd Thd. 48# Baker guide shoe. Set & cemented enghorn and Portland cement. Plug at leted by HOWCO 11:30 PM 5-23-52. Casing shut-off 11:30 AM 5-25-52. Casing shut-off 11:30 AM 5-25-52. By Area Prod. Supt. |