

COORD OF DRILL-STEM AND SPECIAL T 6

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 12.71 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 12 25, 19 55

OIL WELL: The production during the first 24 hours was 704 barrels of liquid of which 99.7% was oil; % was emulsion; % water; and 3% was sediment. A.P.I. Gravity 15.3 deg.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Devonian	Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta	T. Clear Fork	T. Morrison
T. Drinkard	T. Wolfcamp	T. Penn
T. Tubbs	T. State sand	
T. Abo	T. Goodford	
T. Penn		
T. Miss		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	4.850	4.850	Unconsolidated sand				
4.850	5.065	15	Anhydrite & Dolomite				
5.065	9.662	4.597	Dolomite				
9.662	9.705	103	Dolomite & line				
9.705	12.827	3.117	Line				
12.827	12.953	121	Line & shale				
12.953	12.959	6	Line & dolomite				
12.959	12.71	315	Dolomite				
		12.71					

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 20, 1956
Company or Operator Bell Oil Company
Name B. Nevill
Address Box 1967, Hobbs, New Mexico
Position or Title Division Exploitation Engineer