

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

tice of Intention Change Plans		Notice of Intention Temporarily Abando			of Intention L Deeper	
TICE OF INTENTION	x	Notice of Intention		Notice	of Intention	
PLUG WELL		TO PLUG BACK		TO SET I	LINER	
tice of Intention Squeeze		Notice of Intention to Acidize	4		of Intention of (Nitro)	
tice of Intention Gun Perforate		Notice of Intention (Other)	1	Nотісв (Отнез	of Intention	
L CONSERVATION		Hobbs, 1	New Mexico		July	22, 1960
1171 1 D, 11 D 11 11 11 11 11 11 11 11 11 11 11 1		((Place)	••••••••••••••••••••••••••••••	(Dai	te)
tlemen:						
				Second Ve	h41 041 0	T
Following is a Not	tice of Intention to do	certain work as describ	ed below at the	. Socony Mo	1	A
•••••••••••••••••••••••••••••••	(Company or Operator)	Net, T. 16-8	Lease	Well No		in(Unit)
AE 1/4 ME	1/4 of Sec6	, T16-S	R 37-E	VMPM.,	Dean Perm) Pean
(40-acre Subdivision	Cou	•		•		
		•				
		DETAILS OF PR				
11 665 1		DETAILS OF PR INSTRUCTIONS IN				
: 11,643'	(FOLLOW		THE RULES	AND REGULAT		
: 11,643' csg set @ 11,	(FOLLOW	instructions in	cement @	and regular	ions)	
: 11,643' csg set @ 11, ose to run fr	(FOLLOW),645 cemented w	instructions in 1/300 sks. Top	cement @ :	AND REGULATION,645' aly 50' above	ions) • indicated	i free point
: 11,643' csg set @ 11, ose to rum fr salvage csg.	(FOLLOW) ,645 cemented were point indices Spot 50 sks of	//300 sks. Top	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	(FOLLOW) ,645 cemented were point indices Spot 50 sks of	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844.	(FOLLOW),645 cemented were point indicated spot 50 sks of 50 sks regulation Home	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION,645' ely 50' aboveut, spet 50	e indicated sks cement	t plug in 9-5
: 11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844. s. Install r	FOLLOW, 645 cemented were point indicated spot 50 sks of Spot 50 sks	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ : approximate re cag is om 100° to	AND REGULATION AND RE	e indicated sks cement	t plug in 9-5
11,643' csg set @ 11, ose to run fr salvage csg. 4944 to 4844. s. Install r	(FOLLOW),645 cemented were point indicated spot 50 sks of 50 sks regulation Home	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ :	AND REGULATION AND RE	e indicated sks cement ud laden f	t plug in 9-5
csg set @ 11, csg set @ 11, cse to run fr salvage csg. 4944 to 4844. cs. Install r	(FOLLOW),645 cemented were point indicated spot 50 sks of 50 sks regulation Home	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ : approximate re cag is om 100° to	AND REGULATION AND RE	e indicated sks cement ud laden f	t plug in 9-5
csg set @ 11, csg set @ 11, cse to run fr salvage csg. 4944 to 4844. s. Install r	(FOLLOW),645 cemented were point indicated spot 50 sks of 50 sks regulation Home	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ spproximatere cag is on 100' to	and REGULATION,645' ely 50' above cut, spet 50 surface w/m	cons) considerated sks cement and laden file	t plug in 9-5 luid between
csg set @ 11, csg set @ 11, cse to run fr salvage csg. 4944 to 4844. cs. Install r proved	(FOLLOW),645 cemented were point indicated spot 50 sks of 50 sks regulation Home	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ approximate re cag is on 100' to	AND REGULATION AND RE	Company, In or Operator	t plug in 9-5 luid between
csg set @ 11, cs	(FOLLOW),645 cemented was point indicase point indicase spot 50 sks cemented was spot 50 sks regulation Mount	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ approximatere cag is on 100° to Socon By	and REGULATION, 645' ely 50' above cut, spet 50 surface w/m Mobil 011 Compa District Sup Send Communication	cons) company, In or Operator corrected and income regarding with the constructions regarding to the constructions of the constructio	t plug in 9-5 luid between t
pose to run fr salvage csg. 4944 to 4844. gs. Install r pproved	(FOLLOW),645 cemented was point indicase point indicase spot 50 sks cemented was spot 50 sks regulation Mount	/300 sks. Top sator, cut csg a cement plug wher cement plug from	cement @ approximatore cag is com 100° to Socons By	and REGULAT: 10,645' ely 50' above cut, spet 50 surface w/m Mobil 011 Compa	Company, In or Operator tions regarding to 1 Company,	t plug in 9-5 luid between t well to: