

CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

AMENDED REPORT

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> For <input type="checkbox"/>
5. State Oil & Gas Lease No.
V-148

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" - FORM C-101 FOR SUCH PROPOSALS.)OIL WELL ☒ GAS WELL ☐ OTHER Re-Entry

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 19 TOWNSHIP 16S RANGE 37E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3824.6' GR

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐PLUG AND ABANDON ☐
CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Perforate, Treat ☒ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11837'. Prep to test new zone. WIH and perforated 11449-11475' w/11 .50" holes as follows: 11449, 450, 453, 454, 456, 463, 464, 468, 470, 474, 475'. RIH w/tubing and packer. Spot acid on perfs 11449-475' and acidize w/1500 gal 15% mud acid + balls. Swab back and test. No oil or gas. Pull packer and RBP, reset RBP and test. WIH and perforated 10814-10849' w/11 .50" holes as follows: 10814, 15, 17, 18, 19, 21, 10845, 46, 47, 48, 49'. Acidized perforations 10814-10849' w/3500 gal 15% acid w/N2 + ball sealers. Swab back load and test. Swab 1-1/2 bbls/hr - 10% oil, 90% water. Pull packer and tubing. WIH and perforated 10206-10211' w/12 .50" holes. Acidized perforations 10206-10211 w/3500 gals 15% acid. Swab load with show of oil. Treated perforations 10206-211' w/10000 gals 20% Series 72 acid and 5000 gals pad. Swabbed well with show of oil. Pull packer and RBP. Reset RBP and test. WIH and perforated 11203-11284' w/12 .50" holes as follows: 11203, 04, 05' (3 holes); 12249-51' (4 holes-2SPF); 11275, 76, 80, 83, 84' (5 holes). Acidized 11203-11284 w/3500 gal. 15% acid w/N2 + balls. Swab back load and test. Make 5 swab runs. Recovered 1/2 bbl oil and 8-1/2 bbls water. Small amount of gas. Pulled RBP, packer and tubing. WIH and perforated 10292-10713' w/12 holes as follows: 10292, 93, 10303' (3 holes), 10324, 28, 29' (3 holes); 10360, 71, 83' (3 holes), 10690, 10710, 713' (3 holes); GBIH w/tubing and packer and spot acid on perfs 10693-10713 and acidize w/2500 gal 15% NEA. Moved RBP to approximately 10430' and test. Spot acid on perfs 10206' 10383 and acidize w/7500 gal 15% NEA + ball sealers in three stages of acid. Move RBP down to approximately 10730' and packer to approximately 10076' and swab perfs 10206-10713 together.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature of Jerry Sexton

TITLE Production Supervisor

DATE 3-1-83

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY

TITLE

DATE

MAR 3 1983

CONDITIONS OF APPROVAL, IF ANY: