

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

August 22, 1938

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

DUPLICATE

Following is a notice of intention to do certain work as described below at the _____
Continental Oil Company **State K-29** Well No. **1** in **SW/4**
 Company or Operator _____ Lease _____
 of Sec. **29**, T. **16**, R. **37**, N. M. P. M., _____ Field,
Lea _____ County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

We propose to plug and abandon this well, which has been drilled to a total depth of 5305', using the following procedure:

Plug back from total depth of 5305' to 5153' with 50 sacks cement. Plug back from 5153' to 3266' using 12 lb. mud. Plug back from 3266' to 3191' using 25 sacks cement. 9-5/8" casing is set at 3266'. After setting cement plug inside 9-5/8" casing at 3191', attempt will be made to salvage as much of the 9-5/8" casing as may be possible. Hole will then be filled with 12 lb. mud from 3191' to point where 9-5/8" pipe is shot off. Cement plug will be run from this point using 25 sacks cement and balance of hole from that point will be filled with 12 lb. mud to base of 13" surface pipe set at 251'. Hole will be filled with cement from 251' to surface of ground. Suitable marker will be erected and location restored to its original condition.

AUG 22 1938

Approved _____, 19____
 except as follows:

Continental Oil Company

AUG 22 1938

Company or Operator

By *H. L. Johnston* **HOBBS OFFICE**Position **District Supt.**

Send communications regarding well to

Name **H. L. Johnston**Address **Box CC, Hobbs, N.M.**

OIL CONSERVATION COMMISSION,

By *Rose Walker*

Title

Oil & Gas Inspector