

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within **10 days** after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

August 16, 1954  
(Date)

Hobbs, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation  
(Company or Operator)

Lea State "BV"  
(Lease)

Southeastern Drilling Co.  
(Contractor)

Well No. **1** in the **NE**  $\frac{1}{4}$  **NW**  $\frac{1}{4}$  of Sec. **29**

T. **16-S**, R. **37-E**, NMPM., **East Lovington-Penn** Pool, **Lea** County.

The Dates of this work were as follows: **August 12-13, 1954**

Notice of intention to do the work (~~yes~~) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_,  
(Cross out incorrect words)

and approval of the proposed plan (~~yes~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 12 Jts (359') 13-3/8" OD 48# Gr H-40 SS casing. Set and cemented at 379' with a total of 600 sacks Regular Neat cement in 2 stages. 1st stage with 450 sacks. Cement did not circulate. Ran 1-1/2" tubing down outside 13-3/8" casing and found top cement at 69'. Recemented with 150 sacks cement thru 1-1/2" tubing. Circulated approximately 25 sacks. Maximum pressure 280#. Job complete 5:PM 8-11-54.

After waiting over 24 hours, tested 13-3/8" casing with 1000# for 30 minutes. There was no drop in pressure. Drilled cement from 358' to 379'. Tested below shoe with 400# for 30 minutes. There was no drop in pressure.

Witnessed by **Glenn Stach**  
(Name)

**Gulf Oil Corporation**  
(Company)

**Drilling Foreman**  
(Title)

Approved: **OIL CONSERVATION COMMISSION**

*S. J. Stanley*  
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name *[Signature]*

Position **Asst. Area Supt. of Prod.**

Representing **Gulf Oil Corporation**

Address **Box 2167, Hobbs, New Mexico**