

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	<input checked="" type="checkbox"/>	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

6-26-53

Hobbs, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Cities Production Corporation

State "AF"

(Company or Operator)

(Lease)

Parker Drilling Company

Well No. **1** in the **NE** $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **30**

(Contractor)

T **16 S**, R. **37 E**, NMPM., **Undesignated** Pool, **Lea** County.

January 6 & 7, 1953

The Dates of this work were as follows:

Notice of intention to do the work (was) ~~not~~ submitted on Form C-102 on **January 6**, 19**53**
(Cross out incorrect words)

and approval of the proposed plan (was) ~~not~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

State "AF" #1 was drilled to a total depth of 11,795' in lime. 13 3/8" OD H-40 SS Csg was set at 309' and left in the hole, cement circulated. 8 5/8" OD 24# & 32# was set at 4935' and left in hole, cement circulated. The hole was loaded with approximately 641 barrels of 10.4 mud laden fluid. Five plugs of cement were spotted: 100 sacks 11,262' to 11,477'; 30 sacks 11,165' to 11,262'; 100 sacks 10,353' to 10,575'; 50 sacks 7338' to 7500'; 25 sacks of 4869' to 4950' bottom of 8 5/8" Csg, 3 sacks 0' to 10' in top of 8 5/8" Csg. A 4" pipe marker has been installed to mark the abandoned location. Fits have been filled and leveled, location cleared of junk.

Billy Houghton, Tool Pusher for Parker Drilling Company, Tulsa, Oklahoma; W. M. Dickey, Production Foreman, Cities Service Oil Company, Hobbs, New Mexico were in charge of the work.

Witnessed by **C. M. Hartwell** **Cities Service Oil Company** **District Superintendent**
(Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

Oil & Gas Inspector

(Title)

JUN 29 1953

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **C. M. Hartwell**

Position **District Superintendent**

Representing **Cities Service Oil Company**

Address **Box 97, Hobbs, New Mexico**

