

NEW MEXICO OIL CONSERVATION COMMISSION


Santa Fe, New Mexico

Notice of Intention to Drill

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico
Place

Nov. 2, 1939



OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.
Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company State **NO** Well No. **4** in **NW SE**
Company or Operator Lease
of Sec. **31**, T. **18S**, R. **37E**, N. M. P. M., **S. Lovington** Field, **Lea** County

The well is **1980** feet (N.) (S) of the **South** line and **2310** feet

(E) (W.) of the **East** line of **Section 31**

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. **B-7896**, Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is **Skelly Oil Co.**

Address **Tulsa, Oklahoma**

We propose to drill well with drilling equipment as follows:

Rotary tools from top to total depth. Contractor is American Drlg. Co.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
15"	13" OD	40#	New	320'	Cemented	200
9-7/8"	8-5/8" OD	26#	New	3000'	Cemented	500
6-1/4"	5-1/2" OD	17#	New	4550'	Cemented	200

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about **4600** feet.

Additional information: **In cementing the 13" OD Casing the cement will be circulated back into bottom of the cellar. In cementing all the above casing sufficient time shall be allowed for cement to thoroughly set before drilling plug and testing casing shut-off.**

Approved except as follows:

NOV 4 - 1939

OIL CONSERVATION COMMISSION,

By

Roy Garbrough
Title **OIL & GAS INSPECTOR**

SKELLY OIL COMPANY

Company or Operator

By

Position

District Superintendent

Send communication regarding well to

Name

Skelly Oil Co.

Address

Hobbs, New Mexico

