


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



DUPLICATE

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing proposed changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

August 14, 1946

Place

Date

OIL CONSERVATION COMMISSION, Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skally Oil Co., State "O" Well No. 7 in NE/4 SE/4


Company or Operator

Lease

of Sec. 31, T. 16S, R. 37E, N. M., P. M., Lovington Field, Lea County.

N

The well is 660 feet (N.) of the South line and 330 feet (E.) of the West line of the NE/4 SE/4 Sec. 31, 16S, 37E.



AREA 640 ACRES

LOCATE WELL CORRECTLY

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-7896 Assignment No. If patented land the owner is

Address

If government land the permittee is

Address

The lessee is Skally Oil Co.

Address Tulsa, Oklahoma

We propose to drill well with drilling equipment as follows:

Rotary tools from top to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Table with 7 columns: Size of Hole, Size of Casing, Weight Per Foot, New or Second Hand, Depth, Landed or Cemented, Sacks Cement. Rows show casing strings: 15" conductor 20', 11" new 2100', 7-3/8" new 4600'.

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about feet.

Additional information: Approximately 20' of 13" OD casing will be set as conductor and cemented with 20 sz cement. In cementing all the above strings sufficient time will be allowed for cement to thoroughly set before drilling plug and testing for casing shut-off.

Approved AUG 15 1946, 19 except as follows:

Sincerely yours,

Skally Oil Co.

Company or Operator

By

Position Dist. Supt.

Send communications regarding well to

Name Skally Oil Co.

Address Drawer "D", Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy Yarbrough

Title Oil & Gas Inspector

113