Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate natu	ire of noti	ce by checking below:		
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	XX	NOTICE OF INTEN	TION TO SHOOT O	R
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTEN	TION TO PULL OR LTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTEN	TION TO PLUG WE	CLL
NOTICE OF INTENTION TO DEEPEN WELL				
	Hob	bs, New Hexico	- February 21	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico Gentlemen: Following is a notice of intention to do certain wor	rk as desc	cribed below at the		
Skelly Oil Co. Star	te "C"		Well No. 10	in MW/4 SW//
of Sec. 31 , T. 165 , R. 37E		N. M. P. M.,	Unnan	<b>ed</b> Field.
Les Count				
FULL DETAILS ( FOLLOW INSTRUCTIONS IN THE  Drilled to total depth of	OF PROD		OF THE COMMISSIO	
Drilled to total depth of and comented with 700 saciused and coment was circuit	OF PROPERULES AT 3190'.  ks of collated to	Ran 8-5/8" OD	casing to 3190 rton process wa	; s t
Drilled to total depth of and commented with 700 sack	RULES A 3190'. ks of c lated t	Ran 8-5/8" OD sement. Hallibur surface. Will at approximatel	casing to 3190 rton process wa	; s t
Drilled to total depth of and comented with 700 sac used and coment was circulable hours & on February 22 drill plug & test casing	RULES A 3190'. ks of c lated t	Ran 8-5/8" OD sement. Hallibur to surface. Will at approximatel	casing to 3190 rton process wa	s t 11
Drilled to total depth of and commented with 700 sach used and comment was circulable hours & on February 22 drill plug & test casing	RULES A 3190'. ks of c lated t	Ran 8-5/8" OD sement. Hallibur to surface. Will at approximatel	casing to 3190 rton process wall let cement setly 2:00 p.m. will skelly 011 Comp	s t 11
Drilled to total depth of and comented with 700 sac used and coment was circulable hours & on February 22 drill plug & test casing	RULES A 3190'. ks of c lated t	Ran 8-5/8" OD  sement. Hallibur  se surface. Will  at approximatel  f.  By  Position	casing to 3190 rton process wall let cement setly 2:00 p.m. will skelly 011 Comp	any or
Drilled to total depth of and comented with 700 sac used and coment was circulable hours & on February 22 drill plug & test casing	RULES A 3190'. ks of c lated t	Ran 8-5/8" OD  sement. Hallibur  so surface. Will  at approximatel  f.  By  Position  Send co	casing to 3190 cton process wa let cement se ly 2:00 p.m. wil	any or