

Santa Fe, New Mexico

DUPLICATE

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

1/28/52

Place


Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as _____

Skelly Oil Company State OK well No. 10 in NW SW
Company or Operator Lease
of Sec. 31, T. 16N, R. 37E, N. M. P. M., Unnamed Field, Lea County.



AREA 640 ACRES

LOCATE WELL CORRECTLY

The well is 3080 feet N (S.) of the North line and 440 feet (E.) W of the west line of Section 31

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. B-7896 Assignment No. _____

If patented land the owner is _____

Address _____

If government land the permittee is _____

Address _____

The lessee is Skelly Oil Company

Address Tulsa, Okla.

We propose to drill well with drilling equipment as follows: _____

Rotary tools from surface to total depth.

The status of a bond for this well in conformance with Rule 89 of the General Rules and Regulations of the Commission is as follows: _____

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Secks Cement
18"	13-3/8"	44.5	New	300'	Cemented	300
12-1/4"	9-5/8"	36	New	3100'	Cemented	1500
7-7/8"	5-1/2"	17	New	8500'	Cemented	700

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 8300 feet.

Additional information: Halliburton process shall be used in cementing all casing. Cement will be circulated to surface on 13-3/8" & 9-5/8" casing.

JAN 29 1952

Approved _____, 19____
except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By _____

Position District Superintendent

Send communications regarding well to:

Name Skelly Oil CompanyAddress Box 38 - Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By _____

Title _____