NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

District Office, Oil Conservation Commission, within 10 days after the work specified is com-

	Indicate Nature of Report by C	necking Bel	ow Commission	
REPORT ON BEGINNING OPERATIONS	REPORT ON RESULT OF TO	EST	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETS OPERATION	ON	REPORT ON (Other)	
	Jan. 26, 19	53	Habbs, How Ke	Place)
Following is a report on the work of	one and the results obtained under to	ne heading n	oted above at the	
Skelly Oil Company			State WIN	
(Company or Oper	ator)		(Degae)	
Sharp Drilling Co.	, Well N	, 13	in the 38 1/4 IN 1/4	of Sec,
(Contractor)	ndesignated	Pool	Lea	County.
, R., NMPM.,				·
The Dates of this work were as folows:	lan. 23, 1953 thre Janl 2	5, 1953		
Notice of intention to do the work	(was not) submitted on Form C-102 C	М	(Cross out incorrect words)	,
and approval of the proposed plan				
DETAIL	ED ACCOUNT OF WORK DONE	AND PEST	LTS OBTAINED	
	TED VOCABLI AL MARIE DAVE.	THE WING		
Set 5.3 /98 05 engine et 11	OLA! . Committed around	5-1/2" C	D casing shoe with 6	82 sacks
Set 5-1/2" OB casing at 11	, Chi. Commend around	5-1/2" 0	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 13 and comented through two-s	,044'. Commted around stage tool at 8988' with 8988', and tested easing	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 13 and comented through two-s	,044'. Commted around stage tool at 8988' with 8988', and tested easing	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and essented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and essented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and essented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and essented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2° OB easing at 11 and comented through two-stage tool at to 11,044' and tested easifhe Halliburton process we	,044'. Commented around stage tool at 8988' with 8988', and tested easing and shut-off. Tested old	5-1/2" (1300 sec shut-of	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 11 and essented through two-splug to two-stage teel at to 11,044' and tested easi	,044'. Commted around stage tool at 8968' with 8968', and tested easing ing shut-off. Tested oks a used.	5-1/2" (1300 see sinst-of F•	D easing shoe with 60	r erryter
Set 5-1/2" OB easing at 13 and comented through two- plug to two-stage tool at to 11,044' and tested easi The Halliburton process we Witnessed by	Skelly Oil Compa	5-1/2" (1300 sac singt-of y.	Dist. Feetman (Title)	illed plug
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage tool at to 11,044' and tested easing the Halliburton process we witnessed by	Skelly Oil Compa	5-1/2" (1300 sac singt-of y.	Dist. Further at the information given above is	illed plug
Set 5-1/2" OB easing at 11 and comented through two-stage tool at to 11,044' and tested easing the Halliburton process we witnessed by E. R. Bedts Witnessed by (Name)	Skelly Oil Commission Commission The commission Skelly Oil Company Commission The commission Skelly Oil Company Commission The commiss	5-1/2" (1300 sac single-of y.	Dist. Further at the information given above is	illed plug
Set 5-1/2" OB easing at 11 and comented through two-splug to two-stage tool at to 11,044' and tested easing the Halliburton process we witnessed by	Skelly Oil Compact COMMISSION John'. Command around reage tool at 8968' with 8968', and tested easing ing shut-off. Tested oke (Compactor) Compactor to the commission of th	5-1/2" (1900 sade sinct-of	Dist. Further at the information given above is	illed plug
Set 5-1/2" OB easing at 11 and comented through two-stage tool at to 11,044' and tested easing the Halliburton process we witnessed by	Skelly Oil Commission Commission The commission Skelly Oil Company Commission The commission Skelly Oil Company Commission The commiss	5-1/2" (1900 sade sinct-of	Dist. Further at the information given above is	illed plug

(Date)