## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

-1

## MISCELLANEOUS REPORTS ON WELLS

| instructions in the Rules and Regulations of th   | ne Commission  | by an agent of the Commission. So   |                  |
|---|--|---|------------------|
|   | Indicate Nature of Report by Checking Belo   | OW  |                  |
| REPORT ON BEGINNING<br>DRILLING OPERATIONS  | REPORT ON RESULT OF TEST OF CASING SHUT-OFF  | REPORT ON REPAIRING WELL  |                  |
| REPORT ON RESULT<br>OF PLUGGING WELL  | REPORT ON RECOMPLETION OPERATION   | REPORT ON (Other)   |                  |
|   | Feb. 16, 1954  | Hobbs, New Man  | d.ee             |
| m u de la completación de mo  | and the results obtained under the heading ne  | oted above at the   |                  |
|   | Ø4 a 4   | e nOn   |                  |
| Skelly Oil Company or Operator)   | ······   | (Lease)   |                  |
| Sharp Drilling Company  | , Well No29  | in the 118 1/4 88 1/4 of 5  | Sec <b>31</b>    |
| (Contractor)  | ten - Paddeck Pool,  |   |                  |
|   |  |   |                  |
| The Dates of this work were as follows:   | 12, 1954 thru Feb. 15, 1954  |   |                  |
|   |  |   |                  |
| Notice of intention to do the work ( (wa  | s not) submitted on Form C-102 on  | (Cross out incorrect words)   | , 19             |
| and approval of the proposed plan ( wa  |  |   |                  |
|   |  |   |                  |
| TATOTALI MID  | ACCOUNT OF WODE DONE AND RESID   | LINGUISTAINEU   |                  |
| 12 ad to 2017 and not \$-5/88 OD  | ACCOUNT OF WORK DONE AND RESULT CASING At 2047' with 1075 said C 37 hours and drilled out con      | eks coment by Halliburt   | on pro           |
| 12 ad to 2017 and not \$-5/88 OD  |  | eks coment by Halliburt   | en pre<br>ng shu |
| Lied to 2047 and set 8-5/8" Officer to the surface. Wo in-off tested exay.  | enging at 2017; with 1075 say  | eks cement by Halliburte<br>ment plug. Tested casis<br>Dist. Foreman      | on pre           |
| lled to 2047 and set 8-5/8" OD<br>ent circulated to surface. WO   | casing at 2047' with 1075 sand C 37 hours and drilled out con                                      | eks cement by Halliburtenent plug. Tested casi                            | on pre           |
| Lied to 2047 and set 8-5/8" CD met circulated to surface. Wo i-off tested ekay.  Witnessed by E. R. Deits  (Name) | Skelly Oil Company  (Company)  I hereby certify the  | Dist. Foreman  (Title)  |                  |
| Lied to 2047 and set 8-5/8" CD met circulated to surface. Wo i-off tested ekay.  Witnessed by E. R. Deits  (Name) | Skelly Oil Company  (Company)  I hereby certify the to the best of my  (I was a second or company) | Dist. Foreman  (Title)  |                  |
| Lied to 2047 and set 8-5/8" CD met circulated to surface. Wo i-off tested ekay.  Witnessed by E. R. Deits  (Name) | Skelly Oil Company  (Company)  I hereby certify the to the best of my  Name                        | Dist. Foreman  (Title)  |                  |
| Lied to 2047 and set 8-5/8" CD met circulated to surface. Wo i-off tested ekay.  Witnessed by E. R. Deits  (Name) | Skelly Oil Company  (Company)  I hereby certify the to the best of my  Name                        | Dist. Foreman  (Title)  |                  |
| led to 2047 and set 8-5/8" CD mt circulated to surface. Wo self tested ekay.  Witnessed by K. R. Deits  (Name)    | Skelly Oil Company  (Company)  I hereby certify the to the best of my  Name                        | Dist. Foreman  (Title)  at the information given above is true knowledge. | e and co         |