## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well,

	Indicate Nature of Report by Checking E	Selow
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	Sept. 13, 1954,	Hobbs, N.M. (Place)
Following is a report on the work dor	ne and the results obtained under the heading	noted above at the
Skelly Oil Company		State "O"
(Company or Operato		(Lease)
	, Well No <b>22</b>	
16S , R 37E , NMPM LOVIN	gton Paddock Pool, I	. <b>68</b>
he Dates of this work were as follows. Sen	t. 10, 1954 thru Sept. 12, 195	S.L.
	vas not) obtained.  D ACCOUNT OF WORK DONE AND RESU	ULTS OBTAINED
DETAILER 11.11 DETAI		Sacks cement by Halliburton
DETAILER  Lled to TD 6260 and set 52  Seess. WOC 48 hours and dri	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILER  Lled to TD 6260 and set 52  Seess. WOC 48 hours and dri	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILEI  1led to TD 6260; and set 5½  6ess. WOC 48 hours and dri	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILEI  1led to TD 6260; and set 5½  6ess. WOC 48 hours and dri	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILEI lled to TD 6260; and set 5½ cess. WOC 48 hours and dri	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILEI  lled to TD 6260 and set 5½ sess. WOC 48 hours and dri ted okay.	O ACCOUNT OF WORK DONE AND RESUM OD casing at 6105! with 300	Sacks cement by Halliburton
DETAILEI  11ed to TD 6260 and set 52  12ess. WOC 48 hours and drii  12ed okay.  12ed okay.  13ed okay.  15ed okay.  16ed okay.  16ed okay.  16ed okay.	Skelly Oil Co.	Sacks cement by Halliburton casing shut-off. Shut-off
DETAILEI  11ed to TD 6260 and set 52  12ess. WOC 48 hours and driited okay.	DACCOUNT OF WORK DONE AND RESULT OF CASING At 6105' with 300 lled out cement plug. Texted	Sacks cement by Halliburton casing shut-off. Shut-off
DETAILER  lled to TD 6260 and set 52  sess. WOC 48 hours and dri  ted okay.  Vitnessed by	Skelly Oil Ce.  (Company)	Foreman  (Title)  at the information given above is true and come knowledge.
DETAILER  lied to TD 6260° and set 52  less. WOC 48 hours and drived okay.  Witnessed by E. R. Deitz  (Name)	Skelly Oil Ce.  (Company)  I hereby certify th	Foreman  (Title)  at the information given above is true and combined by Halliburton Casing shut-off. Shut-off  Foreman  (Title)
DETAILER  Liled to TD 6260' and set 52  Deess. WOC 48 hours and drived okay.  Witnessed by E. R. Deitz  Approved: OUL CONSERVATION COM	Skelly Oil Ce.  (Company)  I hereby certify the to the best of my.	Foreman  (Title)  at the information given above is true and combined by Halliburton Character and Combined Com