



# FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	10'	10'	Top of Rotary table to ground
10'	40	30	Caliche
40	130	90	Shale & Caliche
130	225	95	Sand & Red Bed
225	347	122	Shale & Caliche
347	1565	1218	Red rock
1565	1575	10	Red rock & Gyp
1575	1868	293	Red rock
1868	1880	12	Anhydrite
1880	2010	130	Red rock
2010	2125	115	Anhydrite
2125	2300	175	" & salt
2300	2763	463	Salt
2763	3477	714	Salt & Anhydrite
3477	3565	88	Lime
3565	3971	406	Anhydrite
3971	4094	123	" & lime
4094	4680	586	Lime - Hard, gray
4680	4690	10	Lime - Soft, oil pay
4690	4735	45	Lime - Mixed, hard & soft, oil pay shows
4735	4880	145	Lime, shale, sand
4880	4900	20	Lime - Hard, gray
4900	4922	22	Lime - Soft, brown, oil pay
4922	4946'	24	Lime - Gray, hard - Bottom 6' contains water.
	4946'		Original total depth.
4946	4938	-	Plugged back with hole savings.
4938	4918	-	Plugged back w/ Dowell Plastic plug
	4918'	-	Present total depth
<p>*At total depth 4946' well tested 10 bbls fluid per hour w/ 12% water content. Was plugged back w/ hole savings &amp; Dowell Plastic plug to 4918' and complete water shutoff was obtained.</p>			