

PRODUCTION ACROSS  
WELL COMMONLYThe Water Associated Oil Company  
(Company or Operator)State WPA Unit

(Lands)

Well No. 14-9, in SE 1/4 of SW 1/4, of Sec. 32, T. 16-8, R. 37-8, N.M.P.M.

## Location Above

County,

Well is 1650 feet from West line and 990 feet from South lineof Section SW-16-8-37-8. If State Land the Oil and Gas Lease No. is R-7897.Drilling Commenced 8-12-54, 19..... Drilling was Completed 10-8-54, 19.....Name of Drilling Contractor Lee Drilling CompanyAddress Midland, TexasElevation above sea level at Top of Derrick Floor 3816. The information given is to be kept confidential until  
Not Confidential, 19.....

## OIL SANDS OR ZONES

No. 1, from 8340' to 8380' No. 4, from..... to.....

No. 2, from..... to..... No. 5, from..... to.....

No. 3, from..... to..... No. 6, from..... to.....

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to..... feet.

No. 2, from..... to..... feet.

No. 3, from..... to..... feet.

No. 4, from..... to..... feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	NUMBER OF PERFORATIONS	PURPOSE
13-3/8"	36#	New	320	Tex-Pattern	None	None	Surface Casing
8-5/8"	32-36#	New	3503	Larkin	"	"	Intermediate
5-1/2"	17#	New	5101	"	"	"	Production
(Tubing)							

## MUDGING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASTING	WEIGHT PER FT	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/8"	13-3/8"	333#	350	Halliburton		
11"	8-5/8"	3495#	1250	"		
7-5/8"	5-1/2"	8411#	532	"		
PIPE 12 8-5/8" @ 3313#						

## RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. of Gals. used, interval treated or shot.)

Before completion this well was acidized with 500 gallons Mud Acid and 500 gallons Regular Acid.

Result of Production Stimulation.....

Depth Cleaned Out 8397'