

A 10x10 grid with a handwritten 'x' in the 4th column and 3rd row from the top-left corner.

## WELL RECORD

AREA 640 ACRES  
LOCATE WELL CORRECTLY

State "P" Unit  
(Lease)

**Not Confidential** 19

No. 3, from.....to..... No. 6, from.....to.....

No. 4. from \_\_\_\_\_ to \_\_\_\_\_ feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	36	New	301	Tex-Pattern	None	None	Surface Casing
8-5/8"	32	"	3487	Larkin	"	"	Intermediate
5-1/2"	17	"	5110	"	"	8350 - 8360	Production

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-3/4"	13-3/8"	297	350	Halliburton		
11"	8-5/8"	3499	1200	"		
7-7/8"	5-1/2"	8420	732	"		
		#Hung in 8-5/8" @ 3333'				

Depth Cleaned Out.....84300

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1120 feet, and from feet to feet.  
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 4-12-55, 19

OIL WELL: The production during the first 24 hours was 313 barrels of liquid of which 200 % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 21.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.  
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	20		T. Devonian		T. Ojo Alamo
T. Salt.			T. Silurian		T. Kirtland-Fruitland
B. Salt.			T. Montoya		T. Farmington
T. Yates	20		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	400		T. Granite		T. Dakota
T. Glorieta	600		T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs	700		T.		
T. Abo	800		T.		
T. Perm. Michigan	1000		T.		
T. Miss.			T.		

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	300	300	surface sands, caliche				Deviation Surveys
300	3010	1719	Red Beds				Degrees
3010	3586	2576	Anhydrite & salt	3000			1/2
3586	4000	4000	same	3000			1/2
				3000			1/2
				3000			3/4
				3000			
				3000			
				3000			1/4
				3000			1/4
				3000			1/2
				3000			1/4
				3000			3/4
				3000			1-1/2
				3000			1-1/2
				3000			1-1/4
				3000			1
				3000			1/4
				3000			1-1/4
				3000			1-3/4
				3000			1-3/4
				3000			1-3/4
				3000			1-1/2
				3000			1-1/4

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

April 22, 1955 (Date)  
Company or Operator: Tide Water Assoc. Inc. Address: 500 E. Hobbs, New Mexico  
Name: A. W. Hagan Position or Title: President