


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



HOBBS OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Helmerich & Payne

415 Philtower, Tulsa, Oklahoma

Company or Operator

Address

STATE C

Well No. #1

in

of Sec. 3

T. 14S

Lease

R. 38E

N. M. P. M.

Field,

Wildcat near Lovington - Lea

County.

Well is 640 feet south of the North line and 640 feet west of the East line of

If State land the oil and gas lease is No. State C #1 Assignment No.

If patented land the owner is State of New Mexico Address

If Government land the permittee is Address

The Lessee is Helmerich & Payne Address 415 Philtower, Tulsa, Okla.

Drilling commenced May 8 1941 Drilling was completed June 13 1941

Name of drilling contractor Helmerich & Payne Address Tulsa, Okla.

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from None to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4	40#	8		216	Bell joint	None	None	None	None

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
7 7/8	10 3/4	216	10 Sacks at 3150			
			8 " " 350			
			2 " " surface		Mud was 10 1/2 pounds - 39 disc.	

PLUGS AND ADAPTERS

Heaving plug—Material None Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
			None			

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from Nothing feet to 5635 feet, and from feet to feet

Cable tools were used from None feet to feet, and from feet to feet

PRODUCTION

Put to producing None 19

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

T. A. Beavers Driller Fred Howe Driller

L. C. Cornett Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 16th

Hobbs, New Mexico

June 16, 1941

Place

Date

day of June 1941

Name Helmerich & Payne

By

Fred Howe

Position

Land Operator

Notary Public

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	210 sand and shell		SAnd and SHell.
210	2225 2282		Red rock and shell.
2225	2312		Anhydrite.
2312	3124		Salt.
3124	4710		Red rock and anhydrite.
4710	5635		Line.