

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Atlantic Richfield Company	8. Farm or Lease Name Reed Estate
3. Address of Operator P. O. Box 1978, Roswell, New Mexico 88201	9. Well No. 2
4. Location of Well UNIT LETTER I 1980 South 660 THE East LINE, SECTION 22 TOWNSHIP 15-S RANGE 38-E NMPM.	10. Field and Pool, or Wildcat Medicine Rock-Devonian
15. Elevation (Show whether DF, RT, GR, etc.) 3718' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well has recently started producing 100% water and no remedial possibilities exist. We propose to plug & abandon as follows:

- Spot ⁴⁰ sack cement plug in 5½" casing from 12780' to 12630'.
- Shoot off and recover 5½" csg as deep as possible (Top of cement @ 8800').
- Spot these cement plugs:
 - 35 sx in and out of 5½" stub.
 - 35 sx across Abo (Top of Abo @ 8210').
 - 35 sx across Glorieta (Top of Glorieta @ 6423').
 - 35 sx in and out of 9-5/8" shoe @ 4880'.
 - 10 sx in top of well.

9# salt gel mud will be used to spot plugs. 13-3/8" and 9-5/8" casing strings will remain intact. Dry hole marker will be installed and location will be cleared and levelled.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Dist. Drlg. Supervisor DATE 1-14-70
APPROVED BY [Signature] TITLE DATE
CONDITIONS OF APPROVAL, IF ANY: