

**DUPLICATE**

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)January 14, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the State AZCities Service Production Company  
(Company or Operator)Well No. 1 in 0  
(Unit)SW  $\frac{1}{4}$  SE  $\frac{1}{4}$  of Sec. 32, T. 16-S, R. 38-E, NMPM., Wildest Pool  
(40-acre Subdivision)Lea County.FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to 13,139' lime. It was plugged back to 5463' in lime. Spotted 100 sacks slo-set cement 13,139'-12,814' (325'); set bridge plug at 11,670' and spotted 100 sacks slo-set cement 11,670'-11,345' (325'); spotted 50 sacks slo-set cement 7400'-7238' (162'); set bridge plug at 5705'; spotted 75 sacks cement 5693'-5450', cut plug to 5460', drilled out to 5480' and dumped 48 gal. hydromite which filled up to 5463'.

Six drill stem tests were run, the well logged to total depth, the San Andres acidized and swabbed with no evidence of oil in commercial quantity.

It is proposed to plug and abandon this well by loading hole with mud; spotting 100 sacks of cement from 5463' to 5017' (8 5/8" casing set at 5191') and spotting 10 sacks of cement in the top of the 8 5/8" casing with a marker. It is proposed to clean-up the location in an approved manner when the pits are dry and the work can be done.

Verbal approval received 1-11-57.

Approved JAN 18 1957, 19.....  
Except as follows:Cities Service Production Company  
Company or OperatorBy [Signature]Position District Superintendent  
Send Communications regarding well to:Approved  
OIL CONSERVATION COMMISSIONBy E. J. Fischer  
Title Engineer District IIName Geo. M. GayerAddress Box 97, Hobbs, New Mexico