NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

TEMPORARILY ARADDON WELL TO PLUG BACK NOTICE OF INTENTION O SQUEEZE NOTICE OF INTENTION O SQUEEZE NOTICE OF INTENTION O SQUEEZE NOTICE OF INTENTION O COUNTERSTON O COUNT			Indicate Nature of Notice by (hecking Be	low	
NOTICE OF INTENTION TO SQUEEZE TO ACRUSEZ TO SECRICATION TO SECRICATION TO SOS LOCATION TO ACRUSEZ	Notice of Intention to Change Plans			x		
NOTICE OF INTENTION (OTHER) NOTHER OF INTENTION (OTHER) NOTICE OF INTENT	Notice of Intention ro Plug Well					
Monument, New Mexico January 27, 1953 Gentlemen: Following is a Notice of Intention to do certain work as described below at the W. W. Hamilton "A" Lease Amerada Petroleum Corporation (Company or Operator) Company or Operator) County. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel © 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abendon the above well - Cement plugs will be see in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mod to fill between plugs - No casing will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set © 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set © 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" © 2489', or 42.2% fill.	Notice of Intention to Squeeze					
AMORA FE, NEW MEXICO Monument, New Mexico (Place) Januarfy 27, 1953 (Date) Content Content Following is a Notice of Intention to do certain work as described below at the W. W. Hamilton "A" Lease Amerada Petroleum Corporation (Company or Operator) C/NW/A SE/4 of Sec. 34. , T. 16-S. , R. 38-E. , NMPM. Knowles FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Opert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be so in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No casing will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 298' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Poproved						
Amerada Petroleum Corporation (Company or Operator) C/NW/k SR/4 of Sec. 34. , T. 16-S , R. 38-E , NMPM, Knowles FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be six in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No easing will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Position Assistant District Superintendent Provided Company or Operator Sand Company or Operator District Superintendent			***************************************)		953
Amerada Petroleum Corporation (Company or Operator) C/NW/k SB/4 of Sec. 34. , T. 16-S , R. 38-E , NMPM, Knowles FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be six in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No easing will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Position Assistant District Superintendent Prosition Assistant District Superintendent	Gentlemen:				(= ===,	
C/NW/t SE// of Sec. 34. , T. 16-S , R. 38-E , NMPM. Knowles Peol Company or Operator Send Compan						
C/NW/k SE// of Sec. 34 , T. 16-S , R. 38-E , NMPM. Knowles Peol Less County. FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be see in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No casin will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Position Assistant District Superintendent Send Company or Operator By. Assistant District Superintendent	Amerada Petr	Company or Operator	ion	····	Well Nol in	J
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be s.o in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No casin will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Position Assistant District Superintendent Send Communication. Superintendent	C/NW/k S	K/4 of Sec. 34	т 16-S р 38-й	NIMBA	Knowles	(Unit)
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) 12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be so in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No casin will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. Position Assistant District Superintendent Seed Company or Operator Position Assistant District Superintendent	Tas			,2 11721 171,	,	P001
12,390' Total Depth - Lime & Chert - Finished drilling 7-7/8" hoel @ 2 AM, 1-26-53 Ran Schlumberger Surveys - Ran Caliper Survey & Dip Meter Survey. It out intention to temporarily abandon the above well - Cement plugs will be so in the following sections: 10350' to 10188'; 9100 to 9003'; 64,50 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No casin will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 24,89', or 42.2% fill.		FUL!	L DETAILS OF PROPOSED	DIANG	E MORT	
intention to temporarily abandon the above well - Cement plugs will be soo in the following sections: 10350' to 10188'; 9100 to 9003'; 6450 to 6353' and from 4750' to 4588'. Heavy mud to fill between plugs - No easing will be pulled from well. Will install cap on top of 8-5/8" casing - 13-3/8" Casing set @ 298' W/200 Sx Cement - Circulated. 8-5/8" Casing set @ 4764' W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489', or 42.2% fill. pproved		(TOTTOTAL	INCORPORAÇÃO O TROCOSTA	PLAN U	F WORK	
8-5/8" Casing set @ 4764! W/1500 Sx Cement - Top of cement outside 8-5/8" @ 2489!, or 42.2% fill. pproved	12,390		INSTRUCTIONS IN THE RUI	LES AND I	REGULATIONS)	AV 3 04 ra
pproved	12,390	Total Depth- Ran Schlumbe intention to in the follo 6353' and fr	INSTRUCTIONS IN THE RUI - Lime & Chert - Finiserger Surveys - Ran Call temporarily abandon to wing sections: 103501 om 47501 to 45881. He	to 101	REGULATIONS) lling 7-7/8" hoel @ 2 rvey & Dip Meter Surve e well - Cement plugs 88; 9100 to 9003; to fill between plugs	will be spot 6450 to
pproved By Operation Assistant District Superintendent Send Communications regarding well to	12,390	Total Depth- Ran Schlumbe intention to in the follo 6353' and fr will be pull	INSTRUCTIONS IN THE RUI - Lime & Chert - Finis erger Surveys - Ran Cal temporarily abandon to wing sections: 10350' om 4750' to 4588'. He ed from well. Will in	the above to 101 cavy mud	REGULATIONS) lling 7-7/8" hoel @ 2 rvey & Dip Meter Surve e well - Cement plugs 88; 9100 to 9003; to fill between plugs ap on top of 8-5/8" ca	will be spot 6450 to
By	12,390	Total Depth-Ran Schlumbe intention to in the follo 6353' and frewill be pull 13-3/8" Casi	INSTRUCTIONS IN THE RUI - Lime & Chert - Finiserger Surveys - Ran Cal temporarily abandon to wing sections: 10350' com 4750' to 4588'. He ed from well. Will in	thed dri tiper Sur the abov to 101 tavy mud stall control	REGULATIONS) lling 7-7/8" hoel @ 2 rvey & Dip Meter Surve e well - Cement plugs 88; 9100 to 9003; to fill between plugs ap on top of 8-5/8" co - Circulated. nt - Top of cement out	will be spot 6450 to 8 - No casing asing -
pproved Send Communications regarding well to		Total Depth-Ran Schlumbe intention to in the follo 6353' and frewill be pull 13-3/8" Casis 8-5/8" Casis	INSTRUCTIONS IN THE RUI - Lime & Chert - Finiserger Surveys - Ran Call temporarily abandon to wing sections: 10350' com 4750' to 4588'. He ed from well. Will in ang set @ 298' W/200 Sx ang set @ 4764' W/1500	to 101 exy mud stall care Coment	REGULATIONS) lling 7-7/8" hoel @ 2 rvey & Dip Meter Surve e well - Cement plugs 88'; 9100 to 9003'; to fill between plugs ap on top of 8-5/8" co - Circulated. nt - Top of cement out @ 2489', or 42.25	will be spot 6450 to saving asing - side 8-5/8" fill.
		Total Depth-Ran Schlumbe intention to in the follo 6353' and frewill be pull 13-3/8" Casis 8-5/8" Casis	INSTRUCTIONS IN THE RUI - Lime & Chert - Finiserger Surveys - Ran Call temporarily abandon to wing sections: 10350' com 4750' to 4588'. He ed from well. Will in ang set @ 298' W/200 Sx ang set @ 4764' W/1500	to 101 exy mud stall care Coment	Petroleum Corporation lling 7-7/8" hoel @ 2 rvey & Dip Meter Surve e well - Cement plugs 88'; 9100 to 9003'; to fill between plugs ap on top of 8-5/8" c: - Circulated. Petroleum Corporation Company or Operator	will be spot 6450 to saving asing - side 8-5/8" fill.
	approvedexcept as follows:	Total Depth-Ran Schlumbe intention to in the follo 6353' and frewill be pull 13-3/8" Casis 8-5/8" Casis	INSTRUCTIONS IN THE RUI Lime & Chert - Finiserger Surveys - Ran Call temporarily abandon to wing sections: 10350' om 4750' to 4588'. He ed from well. Will in mg set @ 298' W/200 Sx mg set @ 4764' W/1500 By	che abov to 101 eavy mud stall coment Sx Cement Amerada	Petroleum Corporation Petroleum Corporation 2489', or 42.25 Petroleum Corporation Company or Operator Operator	will be spot 6450 to 6

Address Drawer D, Monument, New Mexico