

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 5, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation **Rose Haves** Well No. **1** in the

Company or Operator _____ Lease _____
SE/4 SW/4 of Sec. **35**, T. **16-S**, R. **38-E**, N. M. P. M.,
Knowles Field, **Lea** County.

The dates of this work were as follows: **November 4, 1949**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **October 30, 1949**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

12,575' - Total Depth - Line. 12,574' Drilled Out Depth. Ran temperature Survey - Top of cement on outside of 7-5/8" casing 9250', actual fill 3245', ratio of actual to calculated fill 76%. Connected 7-5/8" casing, ran 6-5/8" bit & 2-3/8" O.D. EUE tubing and tested 7-5/8" casing & well head connections with 1500# for 1/2 hour - no pressure drop. Drilled cement to 12,574', circulated hole clean and tested 7-5/8" casing with 1500# for 1/2 hour - no pressure drop. Proceeded with completion operations.

Witnessed by **C. E. Nichols** **Amerada Petroleum Corporation** **Farm Boss**
Name Company Title
Subscribed and sworn before me this _____
7th day of **November** **1949**
[Signature] Notary Public
I hereby swear or affirm that the information given above is true and correct.
Name *[Signature]*
Position **Assistant District Superintendent**
Representing **Amerada Petroleum Corporation**
Company or Operator
My commission expires **10-24-53** Address **Drawer D, Monument, New Mexico**

Remarks:

[Signature]
Name
Title

Handwritten signature or text at the bottom left of the page.