

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

AUG - 21 1950

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

July 31, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation **Rose Haven** Well No. **2** in the
Company or Operator Lease
G/SE/4 SE/4 of Sec. **35**, T. **16-S**, R. **38-E**, N. M. P. M.,
Navajo Field **Lee** County.

The dates of this work were as follows: **July 30, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **July 30,** 19 **50**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4812' - Total Depth - Line. Ran Schlumberger Electrical & Gamma Ray Surveys. Ran total of 138 jts. of 8-5/8" O.D. Casing as follows: 81 jts. 36#, Grade 8440, Range 3, 8-Rd. Thd. S.S. New; 43 jts. 36#, Grade J-55, Range 2, 8-Rd. Thd. S.S. New; 14 jts. 32#, Grade J-55, Range 2, 8-Rd. Thd. S.S. New. Casing set at 4810' and cemented with 1000 sacks Lone Star Common cement mixed 3% Jell, 450 sacks Trinity Regular cement & 50 sacks Incon cement - total of 1500 sacks. Plug to 4728' at 5:37 P.M., 7-30-50. Maximum pump pressure 575#.

Witnessed by **D. F. Purse** **Amerada Petroleum Corporation** **Foreman**
Name Company Title

Subscribed and sworn before me this

31st day of **July**, 19 **50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **Roy Munkrough**

Position **Assistant District Superintendent**

Representing **Amerada Petroleum Corporation**
Company or Operator

My commission expires **10-24-53**

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

DATE **July 31, 1950**

Roy Munkrough
Name
OIL & GAS INSPECTOR
Title