

**OIL CONSERVATION COMMISSION**

## Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

April 10, 1949

Monument, New Mexico

Date \_\_\_\_\_

### Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

**Gentlemen:**

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation

W.H. Hamilton

Well No. 1 in the**Company or Operator**

## Lease

NE-SW

of Sec. 35

T. 16S

R. 38E

N M P M

Wildcat

Field.

Lea

**County.**

The dates of this work were as follows: April 9, 1949

Notice of intention to do the work was (~~SECRET~~) submitted on Form C-102 on April 8, 1949

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

12518' Total Depth, Lime. Ran Schlumberger E.C. Survey & Gamma Ray & Checked bottom @ 12518' Ran 84 jts. 5½" OD Grade E, 20#, 8Rd. Thd. R-2, Smls. Csg. W/1/16" EUE, W/Oversize Cplgs. 199 jts. 5½" OD, 17# J-55, R-3, 8Rd. Thd. Spang SS. Csg. Extremeline (New) & 48 jts. 5½" OD, 17#, N-80, R-3, Spang SS. Csg. (New) & set at 12518' W/5 Baker Centralizers @ 12508-12493-12463-12403' & 8 Weatherford Scratchers @ 12514-12512-12497-12482-12467-12452-12437-12422. Cemented with 800 sacks Trinity slow set cement, first 500 mixed 3% Aquagel, plug stopped at 11,412' with 2900# Pressure @ 12:30 A.M. 4-10-49.

Witnessed by Don Topper Amerada Petroleum Corporation Asst. Dist. Supt.,  
Name Company Title

Subscribed and sworn before me this  
10th day of April 1949

I hereby swear or affirm that the information given above is true and correct.

Name John Smith

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires COMMISSION EXPIRES JANUARY 22, 1958 Address Drewar D. Monument, New Mexico

Remarks:

Date 2/12/49

Roy. Yarbrough  
 Name  
 Title